



# SILVERSTONE

## Hydrogen Series

# Hydrogen H90 ARGB

## Horizontal CPU cooler with 4 heat-pipes and 92mm PWM ARGB fan

- Total height of 48mm, flawless compatibility with the current market's Mini-ITX motherboards and space constrained cases
- 11 bladed high performance 92mm PWM controlled fans, with outstanding balance of cooling and quietness
- Spring screw mounting design included for a firm and straight forward installation for both Intel and AMD platforms\*
- Four Ø6mm copper heat-pipes and aluminum fins for excellent heat conducting efficiency
- Fan included 10 ARGB LEDs which can be controlled by ARGB controllers or capable motherboards\*\*
- Anti-vibrational rubber pads included for additional noise dampening



## Specifications

<b>Model No.</b>	SST-HYH90-ARGB
<b>Application</b>	Intel LGA 2066/2011/1700/1200/115x AMD Socket AM4*
<b>Material</b>	Copper heat pipes with aluminum fins
<b>Fan dimension</b>	92mm (W) x 15mm (H) x 92mm (D)
<b>Speed</b>	500 ~ 2600 RPM
<b>Airflow</b>	45.73 CFM
<b>Air pressure</b>	2.29mmH <sub>2</sub> O
<b>Noise</b>	1.3 ~ 34.6 dBA
<b>Rated voltage</b>	Fan: 12V LED: 5V
<b>Rated current</b>	Fan: 0.21A LED: 0.45A
<b>Bearing</b>	Hydraulic bearing
<b>Life expectancy</b>	30,000 hours
<b>Fan connector</b>	4 Pin PWM & 4-1 Pin ARGB (5V LED)**
<b>Net weight</b>	305g
<b>Dimension</b>	95mm (W) x 48mm (H) x 95mm (D) 3.74" (W) x 1.89" (H) x 3.74" (D)


\* Please use the original backplate on your AMD platform motherboard.

\*\* Please check to make sure the control box and motherboard RGB port that you want to connect are the same as HYH90-ARGB's RGB port definition. Incorrect connection may cause malfunction or damage.




# SILVERSTONE

48mm



## Engineered for SFF applications

With a total height of 48mm in a horizontal layout, allows flawless compatibility with the current market's Mini-ITX motherboards and space-constrained cases



## Superior heat dissipation performance

Equipped with a 92mm fan and 4 high-efficiency copper heat-pipes with aluminum ensuring the best thermal conducting efficiency



## Heatsink optimized fan

HYH90-ARGB fan has a 500 ~ 2600 speed range via PWM control, allowing for tailored performance on demand, keeping acoustic noise level at a minimum while guaranteeing maximum cooling performance when required

