Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: Light Prestige |
|--|
|--|

Supplier's address: Departament Sprzedaży, Torowa 45, 32-050 Skawina, PL

Model identifier: LP-777/1W M BK

| _ | • | | | |
|------|-----|-------|------|------|
| Type | Λt | light | COLL | rca. |
| IVDE | VI. | HEILL | SOU | LC. |

| Type of light 30 | arcc. | | | |
|--|-----------------------------|-------------------------|--|--------------|
| Lighting technology used: | | LED | Non-directional or directional: | NDLS |
| Light source cap-type | | Pady lutownicze | | |
| (or other electri | c interface) | | | |
| Mains or non-m | ains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable | e light source: | No | Envelope: | - |
| High luminance | light source: | No | | |
| Anti-glare shield | 1 : | No | Dimmable: | No |
| | | Product parar | neters | |
| Parameter | | Value | Parameter | Value |
| | | General product p | arameters: | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 6 | Energy efficiency class | Е |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 800 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode pow pressed in W | ver (P _{on}), ex- | 6,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 |
| Outer dimen- | Height | 55 | Spectral power dis- | See image |
| sions without | Width | 404 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 72 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | |
|--|------|------------------------------|-------|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | |
| | | Chromaticity coordi- | 0,440 | | |
| | | nates (x and y) | 0,408 | | |
| Parameters for LED and OLED light sources: | | | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 | | |
| the lumen maintenance factor | 0,96 | | | | |

(a)'-': not applicable; (b)'-': not applicable;

