Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Model	identifier	9290030186
IVICICIEI	meniner:	9/90050160

T	- 6	10 - 1- 1		
IVna	α T	IIσnt	source:	,
IVDC	vı	HEILL	Jourte.	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

				7
Parameter		Value	Parameter	Value
General product parameters:				
	mption in on- 100 h), rounded est integer	7	Energy efficiency class	Е
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500
On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal		7,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50
		0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer	Height	143	Spectral power	See image
dimensions	Width	64	distribution in the	in last page
				Page 1 / 2

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	64	range 250 nm to 800 nm, at full-load	
Claim of equival	Claim of equivalent power ^(a)		If yes, equivalent power (W)	60
			Chromaticity coordinates (x and y)	0,312 0,328
Parameters for I	ED and OLED lig	ht sources:		
R9 colour render	ring index value	0	Survival factor	0,90
the lumen maintenance factor		0,93		
Parameters for LED and OLED mains light sources:				
displacement fac	ctor (cos ф1)	0,70	Colour consistency in McAdam ellipses	6
Claims that a source replaces light source with ballast of a parti	nout integrated	_(b)	If yes then replacement claim (W)	-
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)'-': not applicable; (b)'-': not applicable;

