

Type	Curve
Panel Size (diagonal)	31.5"SS VA
Display Viewing Area (HxV)	697.306 x 392.234 mm
Panel Backlight/ Type	Edge
Display Surface(non-glare/ glare)	Non-glare
Color Saturation	93% DCI-P3, 123% sRGB
True Resolution	3840 x 2160 (UHD)
Pixel Pitch	0.181(H) x 0.181(V) mm
Brightness	350 cd/m2(TYP)
Contrast Ratio	3000:1
Viewing Angle	178°(H)/178°(V)
Display Colors	8 bits
Response Time	1ms MPRT/2ms GTG
Refresh Rate	144 Hz/OC 160 Hz (with DP 1.4)
HDR	VESA DisplayHDR400
Flicker-free	Yes
HBR3	Yes
Connectivity	2 x HDMI 2.1 (support 4K 144Hz 4:4:4 @ DSC enabled or 4K 144Hz 4:2:0) 1 x Displayport 1.4 1 x USB Type-C (Alternate Mode; Upstream port; Power Delivery up to 18W) 3 x USB 3.2 Downstream ports 1 x USB 3.2 Upstream port 1 x Earphone Jack
Speaker	3W x 2
Unique Features	OSD Sidekick Aim Stabilizer Sync Black Equalizer Dashboard Crosshair Timer Counter PiP/PbP Eagle Eye Auto-Update KVM 6 axis Color Control Smart OD HDMI CEC Apply Picture Mode
Power Type	Adapter
Power Consumption	47W*
Power Saving Mode	0.5W
Power Off Mode	0.3W
Voltage	19Vdc,4.74A
Tilt(angle)	-5°~+20°
Swivel(angle)	N/A
Pivot(angle/direction)	N/A

Height Adjustment (mm)	100 mm
VESA Wall Mounting(mm)	100*100 mm
Kensington lock	Yes
Phys. Dimension with Stand(WxHxD)	710.5*555*183.9 mm
Phys. Dimension w/o stand (WxHxD)	710.5*423.3*100.5 mm
Box Dimension (WxHxD)	925(W)*570(H)*198(D)mm
Net Weight with stand (Esti.)	7.8 kg
Net Weight without stand (Esti.)	5.5 kg
Gross Weight (Esti.)	11.98 kg
Accessories	Power cable/HDMI cable/DP cable/USB cable/QSG/Warranty card
Note	*The test condition follows CEC standards. ** To enable OSD Sidekick, it requires connection between PC and monitor with USB (A-Male to B-Male) cable.