



MiVue™

M760D

STARVIS dual cams **STARVIS**
Detachable GPS Rider Dash Cam

- | Sony's premium STARVIS CMOS for dual cams
- | F1.6 large aperture
- | Built-in GPS track recording
- | One-button emergency recording
- | WiFi real-time viewing and backup
- | Mobile App to update firmware
- | IP67 Waterproof design

mio™
all about you

Sony's premium STARVIS sensors for best night footage



Sony's supreme grade STARVIS™ sensors are used for front and rear cams to increase the brightness by up to 4 times compared to general sensors when recording in environments with almost no light.



Daytime/Actual
footage with dual cams



* STARVIS and STARVIS is a trademark of Sony Corporation

Night time/Actual
footage with dual cams

Important moments at the grasp of your hand with one-button emergency recording lock file




Through the GPS multifunction control box installed on the handle, a button can be pressed to activate emergency recording lock file immediately during emergencies or when needed to prevent files from being overwritten.



GPS tracking – Time/location auto-calibration

With integrated GPS tracking, the MiVue™ M760D records your driving speed, location and time which is set automatically.

This is important information for the police and insurance companies.



Integrated WIFI for real-time footage viewing and backup

Immediately back up your videos to your smartphone or share them via the MiVue™ Pro app, with the device's integrated WIFI.

You can also update the MiVue™ M760D firmware with WIFI OTA (Over-the-air) update, ensuring your device is always up to date.



APP Operation
Introduction

High quality, Full HD video recordings

Created to capture every detail, the MiVue™ M760D provides Full HD 1080p footage at 30 fps to ensure that all recorded footage is clear and indisputable.



IP67 waterproof design for the entire device

Made of metal casing and fortified glass lenses, the MiVue™ M760D is IP67 waterproof design for unfailing performance and ensure to use in rainy day.

M760D

Installation Location Marks

Installation locations are for reference only; correct locations are subject to the actual motorcycle for installation.



Suggested installation locations for various types of motorcycles

Precautions

- Washing directly with powerful, high pressure water column is prohibited.
- Avoid covering the built-in WiFi of the Main device with metal objects during installation.
- Face the GPS multifunction control box to the sky to ensure the quality of reception.
- Avoid having the connectors exposed in order to prevent vandalism and malicious disassembly.
- The memory card is a consumable item; it's recommended to purchase dedicated memory cards compatible with dash cams.
- Check whether the memory card needs to be formatted or replaced regularly.
- Excessively powerful collision/impact forces may cause the dash cam to stop recording and shutdown automatically.
- This product requires professional installation; please consult professional installers for installation models.

Mio is not responsible for any damages or losses caused to the motorcycle or personnel due to self-installation or any other reasons not attributable to Mio.

Box contents:



MiVue™ M760D
(Main device includes 32GB memory card)



Front cam signal extension cable
(1.5M)



Rear cam signal extension cable
(1.5M)



3M buckle




12V waterproof power cable set



Cable tie set

Specifications

Image	
Resolution	1920x1080 / 30fps for both front and rear cams
Image sensor	Sony's premium STARVIS™ CMOS used for both front and rear cams; all glass lens
Aperture	Front and rear F1.6 large aperture
Video format	.mp4(H.264)
cam angle	Front and rear 130° super wide-angle
Hardware	
WiFi	V
Built-in GPS	V
G-sensor collision sensor	V
Memory card slot	32GB memory card included (refer to *Explanation 1 for details)
Operating temperature	-10° to 60°C
Dimensions & Weight	Main device (not including cables): 60 x 60 x 22 mm / Weight (including cables): 80g Camera (not including cables): 40 x Ø30 mm / Weight (including cables): 52g Control box (not including cables): 57 x 26 x 16.5 mm / Weight (including cables): 100g *Front cam cable length: 1.5m *Rear cam cable length: 1.5m
Input power	DC 12V
Built-in Super capacitor	V
Microphone	V
Waterproof design	Waterproof design for entire machine
One-button emergency recording	V
Software	
Video backup	Perform backup through mobile App To download the App please search for MiVue™ Pro 
OTA update	V (dash cam firmware data can be updated through the MiVue™ Pro App; please keep the power on while updating.)

Explanation 1:

Recommended MicroSD card Class 10 or above, with a maximum support of 128GB; if a 128GB memory is used, the memory card must be placed in the machine and formatted first before it can be used. When recording with dual cams, the memory card must be at least 16GB (Class 10 or above). SanDisk Ultra series memory cards not supported; memory cards manufactured with MLC process or dedicated “dash cam” memory cards recommended.



www.mio.com

©2019 MITAC Digital Technology Corp. All rights reserved. The characteristics of this product are subject to change without notice. All trademarks are the property of their respective owners. All specifications are subject to change without prior notice.