

PRODUCT DATASHEET

SMART+ WIFI OUTDOOR WALL CAMERA CONTROL DG

SMART+ CAMERA CONTROL | Slim wall luminaire with in-app direction adjustable camera, speaker, motion and daylight sensor



Areas of application

- Garages
- Entrance areas
- Outdoor use (IP44)

Product benefits

- Easy and quick installation
- Increased perception of safety thanks to high brightness

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Type of protection: IP44
- HD Live view camera
- Built in speaker and alarm siren
- Luminous flux: 900 lm



TECHNICAL DATA

Electrical data

Nominal wattage	16.00 W
Nominal voltage	220...240 V
Nominal current	73 mA
Mains frequency	50...60 Hz
Power factor λ	> 0.5
Operating mode	Mains voltage

Photometrical data

Light color (designation)	Warm White
Standard deviation of color matching	< 6 sdcm
Nominal luminous flux	900 lm
Luminous flux	900 lm
Luminous efficacy	60 lm/W
Color temperature	3000 K
Color rendering index Ra	> 80
Flickering metric (Pst LM)	≤ 1 %
Stroboscope effect metric (SVM)	≤ 0.4

Light technical data

Beam angle	207.50 °
Starting time	< 0.5 s

Dimensions & Weight

Product weight	850.00 g
Length	120.00 mm
Width	80.00 mm
Height	320.00 mm

Lifespan

Number of switching cycles	12500
Lifespan	25000 h

Colors & materials

Product color	Dark gray
Housing color	Dark gray
Body material	Plastic
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Mounting location	Wall
-------------------	------

Capabilities

Dimmable	Yes
Type of connection	Terminal, 3-Pole (L, N, PE)
Compatible smart home technology	Google Assistant / Amazon Alexa
LED module replaceable	Not replaceable


Certificates & Standards

Energy efficiency class	D
Standards	CE / UKCA
Protection class	I
Type of protection	IP44
EEL – Energy Label	D

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- Complete mounting and connecting accessories included

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction SMART OUTD WIFI WALL CAMERA

DOWNLOAD DATA



Declarations of conformity
SMART OUTD WIFI WALL CAMERA



Declarations of conformity
SMART OUTD WIFI FLOOD CAMERA REM DG

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075564602	Folding box 1	347 mm x 122 mm x 147 mm	950.00 g	6.22 dm ³
4058075564619	Shipping box 4	370 mm x 260 mm x 329 mm	4255.00 g	31.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.