

OVERVIEW



| 1. NOVO button hole | 5. Power connector * |
|------------------------------|--|
| 2. Card reader | 6. USB-C 3.2 Gen 1 |
| 3. USB 3.2 Gen 1 | 7. HDMI 1.4b |
| 4. USB 3.2 Gen 1 (Always On) | 8. Headphone / microphone combo jack (3.5mm) |

Notes:

• Ports with * are only available on selected models



PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 3 / 5 / 7 Processor

Processor**

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Memory Support | Processor Graphics |
|----------------------|-------|---------|-------------------|------------------|--------------------|-------------------|-------------------------|
| AMD Ryzen 3 5300U | 4 | 8 | 2.6GHz | 3.8GHz | 2MB L2 / 4MB L3 | DDR4-3200 | AMD Radeon™ Graphics |
| AMD Ryzen 5 5500U | 6 | 12 | 2.1GHz | 4.0GHz | 3MB L2 / 8MB L3 | DDR4-3200 | AMD Radeon Graphics |
| AMD Ryzen 7 5700U | 8 | 16 | 1.8GHz | 4.3GHz | 4MB L2 / 8MB L3 | DDR4-3200 | AMD Radeon Graphics |

Operating System

Operating System**

- Windows® 11 Pro 64
- Windows 11 Home 64
- Windows 11 Home in S mode
- Windows 10 Pro 64
- Windows 10 Home 64
- · Windows 10 Home in S mode
- · No operating system

Graphics

Graphics

| Graphics | Туре | Memory | Key Features |
|---------------------|------------|--------|--------------|
| AMD Radeon Graphics | Integrated | Shared | DirectX® 12 |

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C)

- HDMI supports up to 3840x2160@30Hz
- USB-C supports up to 3840x2160@60Hz

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory[1]

- · 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

Memory Slots**

- Memory soldered to systemboard, no slots (4GB model)
- · Memory soldered to systemboard, no slots, dual-channel (8GB or 16GB model)

Memory Type

DDR4-3200

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.



Storage

Storage Support

- · Model with 70Wh battery: one drive, 1x M.2 SSD
 - M.2 2242 SSD up to 512GB
 - M.2 2280 SSD up to 512GB
- Model with 45Wh or 57Wh battery: up to two drives, 1x 2.5" HDD + 1x M.2 SSD
 - 2.5" HDD up to 1TB
 - M.2 2242 SSD up to 512GB
 - M.2 2280 SSD up to 512GB

Storage Slot

- Model with 45Wh or 57Wh battery: one 2.5" drive slot + one M.2 slot
 - One 2.5" drive slot, supports 2.5" SATA HDD
 - One M.2 2280 PCle® Gen 3x4 slot, supports M.2 2242/2280 SSD
- Model with 70Wh battery: one M.2 slot
 - One M.2 2280 PCIe Gen 3x4 slot, supports M.2 2242/2280 SSD

Storage Type**

| Disk Type | Interface | RPM | Security |
|---------------|-------------------------|------|----------|
| 2.5" SATA HDD | SATA 6Gb/s | 5.4K | - |
| M.2 2242 SSD | PCIe NVMe®, PCIe 3.0 x4 | - | - |
| M.2 2280 SSD | PCIe NVMe, PCIe 3.0 x4 | - | - |

Removable Storage

Optical

None

Card Reader

4-in-1 card reader (SD, SDHC, SDXC, MMC)

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby® Audio™

Microphone

Dual array microphone

Camera

720p, with privacy shutter, fixed focus

Battery

Battery**

- Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W or 95W AC adapter
- Integrated Li-Polymer 57Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W or 95W AC adapter
- · Integrated Li-Polymer 70Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 95W AC adapter

Max Battery Life[1]

- MobileMark® 2014: 11.5 hr (45Wh)
- MobileMark 2014: 14 hr (57Wh)
- MobileMark 2014: 17 hr (70Wh)

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter



Power Adapter**

- 65W round tip (2-pin, wall-mount) AC adapter, 100-240V, 50-60Hz
- 65W round tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 65W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 95W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

DESIGN

Display

Display**[1]

| Size | Resolution | Touch | Туре | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Viewing Angle | Key Features |
|-------|--------------------|-----------------|------|------------|----------------|-----------------|-------------------|----------------|------------------|-----------------|
| 15.6" | FHD (1920x1080) | None | TN | 250 nits | Anti- glare | 16:9 | 400:1 | 45% NTSC | 90° | - |
| 15.6" | FHD (1920x1080) | None | IPS | 300 nits | Anti- glare | 16:9 | 800:1 | 45% NTSC | 170° | - |
| 15.6" | FHD (1920x1080) | None | IPS | 300 nits | Anti- glare | 16:9 | 1200:1 | 100% sRGB | 170° | - |
| 15.6" | FHD (1920x1080) | Multi- touch | IPS | 300 nits | Anti- glare | 16:9 | 800:1 | 45% NTSC | 170° | - |

Touchscreen

- Capacitive-type on-cell multi-touch, supports 10-point touch
- Non-touch

Notes:

1. California Electronic Waste Recycling Fee

In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to https://www.calrecycle.ca.gov/Electronics/Consumer

Input Device

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight

- · LED backlight
- No support

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 69 x 104 mm (2.72 x 4.09 inches)

Mechanical

Dimensions (WxDxH)

| Models | Dimensions |
|--|--|
| Aluminium (top), aluminium (bottom) models | 356.67 x 233.13 x 16.9-19.1 mm (14.04 x 9.18 x 0.67-0.75 inches) |
| Aluminium (top), PC + ABS (bottom) models | 356.67 x 233.13 x 17.9-19.9 mm (14.04 x 9.18 x 0.7-0.78 inches) |

Weight[1]

| Models | Weight |
|------------|--------------------|
| All models | 1.66 kg (3.66 lbs) |

Case Color**

- · Abyss blue
- Graphite grey
- Platinum grey

Surface Treatment

Anodizing



Case Material**

- Aluminium (top), aluminium (bottom)
- Aluminium (top), PC + ABS (bottom)

Notes:

1. The system weight varies depending on configurations.

CONNECTIVITY

Network

Onboard Ethernet

No Ethernet

WLAN + Bluetooth®**

- 802.11ac 2x2 Wi-Fi® + Bluetooth 5.0, M.2 card
- Wi-Fi 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 Card

Ports^[1]

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C 3.2 Gen 1 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.2)
- 1x HDMI 1.4b
- 1x Card reader
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports

1x Power connector (model with plastic bottom)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s:

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

Thunderbolt™ 3: 40 Gbit/s;

FireWire 400: 400 Mbit/s;

FireWire 800: 800 Mbit/s

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

Fingerprint Reader

- Touch style fingerprint reader on power button
- · No fingerprint reader

BIOS Security

- Administrator password
- User password
- Master hard disk password
- User hard disk password

Other Security

Camera privacy shutter

SERVICE



Warranty

Base Warranty**[1]

- 1-year depot service
- 1-year depot with 2-year system board service
- 2-year (1-yr battery) depot service
- 3-year (1-yr battery) depot service

Notes:

1. More information of warranty policy, please access https://pcsupport.lenovo.com/warranty

ENVIRONMENTAL

Operating Environment

Temperature[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altituda

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications

Green Certifications

- ENERGY STAR® 8.0
- ErP Lot 3
- · RoHS compliant
- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







AMD∄



AMD



AMD**∄**





MD M