

PRODUCT DATASHEET

SMART+ WIFI OUTDOOR FLOOD CAMERA CONTROL DG

SMART+ FLOOD CAMERA CONTROL | Floodlight with in-app direction adjustable camera, speaker, motion and daylight sensor



Areas of application

- Garages
- Entrance areas
- Outdoor use (IP44)

Product benefits

- Easy and quick installation
- Increased perception of safety thanks to high brightness

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Adjustable head
- Type of protection: IP44
- HD Live view camera
- Built in speaker and alarm siren
- Luminous flux: 2,000 lm



TECHNICAL DATA

Electrical data

Nominal wattage	23.00 W
Nominal voltage	220...240 V
Nominal current	104 mA
Mains frequency	50...60 Hz
Power factor λ	> 0.5
Operating mode	Mains voltage

Photometrical data

Light color (designation)	Warm White
Standard deviation of color matching	< 6 sdcn
Nominal luminous flux	2000 lm
Luminous flux	2000 lm
Luminous efficacy	87 lm/W
Color temperature	3000 K
Color rendering index Ra	> 80
Flickering metric (Pst LM)	≤ 1 %
Stroboscope effect metric (SVM)	≤ 0.4

Light technical data

Beam angle	106.20 °
Starting time	< 0.5 s

Dimensions & Weight

Product weight	1100.00 g
Length	200.00 mm
Width	197.00 mm
Height	262.00 mm

Lifespan

Number of switching cycles	12500
Lifespan	25000 h

Colors & materials

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Mounting location	Wall
-------------------	------

Capabilities

Dimmable	Yes
Type of connection	Terminal, 3-Pole (L, N, PE)
LED module replaceable	Not replaceable



Certificates & Standards

Energy efficiency class	D
Standards	CE / ERP / UKCA
Protection class	II
Type of protection	IP44
EEL – Energy Label	D

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- Complete mounting and connecting accessories included

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction SMART OUTD WIFI FLOOD CAMERA
	Declarations of conformity SMART OUTD WIFI FLOOD CAMERA REM DG

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075564626	Folding box 1	262 mm x 212 mm x 177 mm	1249.00 g	9.83 dm ³
4058075564633	Shipping box 4	538 mm x 440 mm x 214 mm	5767.00 g	50.66 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.