

PRODUCT DATASHEET SMART+ WIFI OUTDOOR CASCADE 50CM Post

SMART+ CASCADE MULTICOLOR | Luminaire with WIFI technology



Areas of application

- General illumination
- Gardens
- Patios, balconies

Product benefits

- Easy and quick installation
- Colorful garden lighting with smart and intelligent control options

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Network protocol: WiFiType of protection: IP44



TECHNICAL DATA

Electrical data

| Nominal wattage | 10.00 W |
|------------------------|---------------|
| Nominal voltage | 220240 V |
| Nominal current | 72 mA |
| Mains frequency | 5060 Hz |
| Power factor λ | ≥0.5 |
| Operating mode | Mains voltage |

Photometrical data

| Light color (designation) | Warm White |
|--------------------------------------|------------|
| Standard deviation of color matching | < 6 sdcm |
| Nominal luminous flux | 420 lm |
| Luminous flux | 420 lm |
| Luminous efficacy | 38 lm/W |
| Color temperature | 3000 K |
| Color rendering index Ra | ≥80 |
| Flickering metric (Pst LM) | ≤1 % |
| Stroboscope effect metric (SVM) | ≤0.4 |

Light technical data

| Beam angle | 270 ° |
|---------------|---------|
| Starting time | < 0.5 s |

Dimensions & Weight

| Product weight | 1594.00 g |
|----------------|-----------|
| Length | 200.00 mm |
| Width | 160.00 mm |
| Height | 500.00 mm |

Lifespan

| Number of switching cycles | 12500 |
|----------------------------|---------|
| Lifespan | 25000 h |

Colors & materials

| Product color | Dark gray |
|----------------|-----------|
| Housing color | Dark gray |
| Body material | Aluminum |
| Cover material | Glass |

Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|---------------------------|-----------|
| | |

Additional product data

Capabilities

| Dimmable | Yes | |
|--|---------------------------------|--|
| Type of connection Terminal, 3-Pole (L, N, PE) | | |
| Compatible smart home technology | Google Assistant / Amazon Alexa | |
| LED module replaceable Not replaceable | | |

Certificates & Standards

| Energy efficiency class | F |
|-------------------------|-----------|
| Standards | CE / UKCA |
| Protection class | 1 |
| Type of protection | IP44 |

EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

DOWNLOAD DATA

| | DOWNLOAD DATA |
|-----|-------------------------------------|
| PDF | User instruction SMART WIFI CASCADE |

DOWNLOAD DATA



Declarations of conformity EC_SMART OUTD WIFI

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075564268 | Folding box 1 | 222 mm x 182 mm x 522 mm | 2104.00 g | 21.09 dm³ |
| 4058075564275 | Shipping box 2 | 540 mm x 380 mm x 250 mm | 5061.00 g | 51.30 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.