MSI Motherboard MAG B760 TOMAHAWK WIFI DDR4 s1700 4DDR4 ATX

Basic information

Producer: MSI AB Code: KBMSIIIEB760A02 Vendor Code: MAG B760 TOMAHAWK WIFI DDR4 EAN Code: 4711377026376 Guarantee: 3 years



Parameters

Model	MAG B760 TOMAHAWK WIFI DDR4
CPU socket:	
Processor family:	
-	Intel Pentium Gold
Processor family:	
Processor family:	
Processor family:	
Processor family:	
Integrated CPU:	
Chipset manufacturer:	Intel
Chipset type:	INTEL B760
Memory type :	DDR4
Number of DDR4 slots:	4
Memory bus frequency:	2133 MHz
Memory bus frequency:	2400 MHz
Memory bus frequency:	2666 MHz
Memory bus frequency:	
Memory bus frequency:	
Memory bus frequency:	
Memory bus frequency:	3800 MHz
Memory bus frequency:	4000 MHz
Memory bus frequency:	4200 MHz
Memory bus frequency:	4266 MHz
Memory bus frequency:	4400 MHz
Memory bus frequency:	
Memory bus frequency:	
Memory bus frequency:	
Memory bus frequency:	
Memory bus frequency:	
Memory bus frequency:	
Max memory size :	
Expansion slots:	
Expansion slots:	1 x PCle 4.0 x 1
Expansion slots:	
Max. number of SATA devices :	4
RAID: Yes	
Detailed data on disk/drive interfaces:	3 x M.2: M.2_1 (from CPU) supports up to PCle 4.0 x4, supports 22110/2280/2260/2242 devices M.2_2 (from chipset) supports up to PCle 4.0 x4, supports 2280/2260/2242 devices M.2_3 (from chipset) supports up to PCle 4.0 x4 / SATA mode, supports 2280/2260/2242 devices 4 x SATA 6G
	HDMI DisplayPort Supports HDMITM 2.1 with HDR, maximum resolution 4K 60Hz Supports DP 1.4, max resolution 8K 60Hz *Available only on processors with integrated graphics. Graphics specifications may vary depending on the installed processor.
	Realtek ALC897 Codec 7.1-Channel USB High Performance Audio S/PDIF out
	1 x 10/100/1000/2500 Mbit/s
	Wi-Fi 802.11a/b/g/n/ac/ax
Network interface:	
Network interface:	LAN: Realtek 2.5Gbps LAN Wireless communication: Intel WiFi 6E The wireless module is pre-installed in the M.2 (Key-E) slot. Supports MU-MIMO TX/RX, 2.4GHz/5GHz/6GHz* (160MHz) up

	to 2.4Gbps Supports 802.11 a/b/g/n/ac/ax
	Bluetooth 5.3, FIPS, FISMA
USB ports at back panel:	
USB ports on motherboard:	
Number of USB 3.0/USB 3.1 gen 1/USB 3.2 gen 1 ports:	
Number of USB 3.1/USB 3.1 gen 2/USB 3.2 gen 2 ports:	
FireWire (IEEE 1394):	No
COM connector / port:	No
LPT connector / port:	No
External connectors:	1 x DisplayPort
External connectors:	1 x HDMI
External connectors:	1 x Central Speaker / Subwoofer
External connectors:	1 x Rear Speaker
External connectors:	1 x Line In
External connectors:	1 x Line Out
External connectors:	1 x MIC
External connectors:	1 x RJ-45
External connectors:	1 x S/PDIF
External connectors:	4 x USB 2.0
External connectors:	4 x USB 3.1
External connectors:	1 x USB 3.1 Type-C
External connectors:	2 x SMA
Onboard connectors:	1 x 4pin CPU fan
Onboard connectors:	5 x 4pin Chassis fan
	1 x 4-pin water-pump-fan
Onboard connectors:	1 x 24pin ATX zasilanie
Onboard connectors:	3 x M.2
Onboard connectors:	4 x SATA III 6Gb/s
Onboard connectors:	4 x USB 2.0/1.1
Onboard connectors:	2 x USB 3.0 header
Onboard connectors:	1 x USB C
Onboard connectors:	1 x TPM header
Onboard connectors:	2 x System panel header
	1 x Front panel audio header
Onboard connectors:	•
Onboard connectors:	1 x Chassis intrusion header
	1 x RGB LED strip header
Onboard connectors:	•
Special functions:	
BIOS:	
Form factor:	ATX
	243.84 x 304.8 mm
Accessories included:	
Supported operating systems:	
Supported operating systems:	
Software:	
Other information :	