## Technical parameters of the model and declared values

Commission Delegated Regulation (EU) 2019/2013 of 11 March 2019 supplementing Regulation (EU) 2017/1369 of the European Parliament and of the Council with regard to energy labelling of electronic displays and repealing Commission Delegated Regulation (EU) No 1062/2010 (Text with EEA relevance).

	Parameter	Declared parameter value			Unit
Gen	eral				
1	Supplier's name or trade mark	Šilelis			
2	Model identifier	TV-322			
3	Energy efficiency class for Standard Dynamic Range (SDR)	Е			A – G
4	On mode power demand in Standard Dynamic Range (SDR)	26,0			W
5	Energy efficiency class for High Dynamic Range (HDR), if implemented	n.a.			A – G
6	On mode power demand in High Dynamic Range (HDR)	-			W
7	Off mode, power demand	0,5			W
8	Standby mode power demand	0,5			W
9	Networked standby mode power demand			2,0	W
10	Electronic display category	Television			
11	Size ratio	16	:	9	
12	Screen resolution (pixels)	1 366	Х	768	
13	Screen diagonal			80,0	cm
14	Screen diagonal			32	inches
15	Visible screen area			27,4	dm²
16	Panel technology used	LED LCD			
17	Automatic Brightness Control (ABC) available	No			
18	Voice recognition sensor available	No			
19	Room presence sensor available	No			
20	Image refresh frequency rate (normal configuration)			60	Hz
21	Minimum guaranteed availability of software and firmware updates (from the date of end of the placement on the market (as set out in Annex II E, point 1 of Commission Regulation (EU) 2019/2021)			2	Years
22	Minimum guaranteed availability of spare parts (from the date of end of the placement on the market, as set out in Annex II E, point 1 of Commission Regulation (EU) 2019/2021)			2	Years
23	Minimum guaranteed product support (from the date of end of the placement on the market, as set out Annex II E, point 1 of Commission Regulation (EU) 2019/2021)			2	Years

	Minimum duration of the general guarantee offered by the supplier	2	Years					
For	For On-mode							
24	Peak white luminance of the brightest on mode configuration	-	cd/m²					
25	Peak white luminance of the normal configuration	-	cd/m²					
26	Peak white luminance ratio (calculated as value of 'Peak white luminance of the normal configuration'	-	%					
	divided by value of 'Peak white luminance of the brightest on mode configuration' multiplied by 100)							
For	Auto Power Down (APD)							
27	Length of time in on mode before the electronic dis- play automatically switches to standby, off mode, or another condition which does not exceed the applic- able power demand requirements for off mode or standby mode	240:00	mm:ss					
28	For televisions: the length of time, following the last user interaction, before the television automatically switches to standby, off-mode, or another condition which does not exceed the applicable power consumption requirements for off-mode or standby-mode	240:00	mm:ss					
29	For televisions equipped with room presence sensor: the length of time, when no presence is detected, before the television automatically switches to standby, off-mode, or another condition which does not exceed the applicable power demand requirements for off mode or standby mode	-	mm:ss					
30	For electronic displays other than televisions and broadcast displays: the length of time, when no input is detected, before the electronic display automatically switches to standby, off-mode, or another condition which does not exceed the applicable power consumption requirements for off mode or standby mode	-	mm:ss					
For	ABC							
	railable and activated by default		1					
31	Percentage of power reduction due to ABC action between the 100 lux and 12 lux ambient light conditions	-	%					
32	On mode power at 100 lux ambient light at the ABC sensor	-	W					
33	On mode power at 12 lux ambient light at the ABC sensor	-	W					
34	Screen luminance at 100 lux ambient light at the ABC sensor (1)	-	cd/m²					
35	Screen luminance at 60 lux ambient light at the ABC sensor (1)	-	cd/m²					

36	Screen luminance at 35 lux ambient light at the ABC sensor (1)	-	cd/m²				
37	Screen luminance at 12 lux ambient light at the ABC sensor (1)	-	cd/m²				
For Power Supply							
38	Power supply type	Internal					
39	Standard references (if relevant)	-	TEXT				
40	Input voltage	-	V				
41	Output voltage	-	V				
42	Input current (max)	-	Α				
43	Output current (min)	-	Α				

<sup>(1)</sup> the values of ABC luminance-related parameters are indicative, and the verification is against the applicable ABC-related requirements.