



6-Port USB Charging Station

Six USB-A Ports, up to 5 V / 2.4 A per Port, 50 W Total Output, Black

Part No.: 102254

EAN-13: 0766623102254 | UPC: 766623102254

6-Port USB Charging Station — Keep your portable devices fully powered and secure.

Portable USB electronics place heavy demands on their batteries for power and the Manhattan 6-Port USB Charging Station helps keep your tablets, mobile phones, digital cameras and other devices charged and ready to go. This charging station plugs into any standard wall outlet and offers rapid charging. With 50 W total power output, the station offers Smart IC technology to optimize device charging. Each port supports up to 5 V / 2.4 A to fast charge smartphones and other handheld devices. Plus, it smartly protects itself and your devices from short-circuits, over-voltage, over-current and overheating.

The Manhattan 6-Port USB Charging Station is a great way to charge the devices you use most, whether at home, school or the office. It features six wide bays for securing most devices — with cases — while charging, keeping your countertop clean and clutter-free.

Features:

- Six USB-A charging ports for tablets, smartphones and other portable devices
- Each port supports up to 5 V / 2.4 A
- Smart IC for ideal power allocation
- Overload, overcurrent and overheating protection
- Features built-in LED light
- Sturdy, compact and heavy-duty; perfect for desktop charging for home, office, etc.



manhattan-products.com

• Three-year warranty

Specifications:

Standards and Certifications

- CE
- FCC
- RoHS
- WEEE
- ETL

Ports

Six USB-A charging ports

Output Characteristics

• USB-A outputs: 5 V; maximum 2.4 A; 50 W

Input Characteristics

• AC rated voltage: 100 - 240 V

• Frequency range: 50 - 60 Hz (±1 Hz)

• Current: ≤ 1 A at 100 VAC 60 HZ

Output Characteristics

• Rated voltage: 5 V

• Current: 2.4 A maximum (at constant voltage mode)

• Rated power: 50 watts maximum

Overshoot voltage: ≤ 5%

Protection Characteristics

- Short-circuit (SCP) with auto-recovery mode
- Overvoltage (OVP) with auto-recovery mode
- Overcurrent (OCP) current limit: 150% (max)
- Over-temperature (OTP)

Physical

Dimensions: 15.5 x 12.5 x 7.62 cm (6.1 x 4.92 x 3 in.)

• Bay width: 27 mm (1.06 in.) each

• Weight: 0.42 kg (0.94 lbs oz.)

· Housing: plastic

Operating Environment

• Operation Temperature: 0 - 30°C (32 - 86°F)

• Storage Temperature: -20 - 65°C (-4 - 149°F)

• Humidity (noncondensing): 10 - 90%

Package Contents

• 6-Port USB Charging Station



manhattan-products.com

- 1 m (3.3 ft.) Power cord
- Instructions









