

FCS-4072, GEMINI PTZ IP Camera, 4-MP, 32x Zoom, H.265, IR 200M, Indoor/Outdoor

Product Images



Short Description

- 4-Megapixel high-definition resolution
Built-in Micro SD/SDHC card slot for local storage
- Dual power support: 24V AC/PoE
- Video compression: H.265, H.264, MJPEG
- Weatherproof IP66-rated housing
- Supports 32X optical zoom
- Simultaneous Third Streams
- 200 Meter IR Distances
- Support Audio Alarm /Flashing Alarm.

Description

The LevelOne FCS-4072 is a PTZ IP surveillance camera designed for use outdoors, boasting 4-Megapixel resolution and a 32X optical zoom. The camera features motorized Pan and Tilt features as well, enabling it to focus in a variety of directions and zoom in on a specific viewing area, and 200 meter IR led for night view clear. The camera is also PoE, enabling it to run both power and data on the one Cat.5 cable, making deployments easy and efficient. An IP66-rated weatherproof casing allows for safe, reliable operation in outdoor conditions such as rain, heat, dust, snow and humidity.

Additional Information

Harmonized System (HS) code	852589
Customs product code (TARIC)	8525890000
Features	Face capture: Up to 5 faces captured at the same time: Supports detecting, capturing, grading, selecting of face in motion, and output the best face picture of the face. Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection, audio exception detection. Manual tracking, auto-tracking 24 programmable polygon privacy masks Support Audio Alarm /Flashing Alarm.
PoE Supported	Yes
2-way audio	Yes
DI/DO	Yes
IR LED for night vision	Yes
Max. Resolution	4 Megapixels
Resistance	Weatherproof
IP Camera series	GEMINI
Camera Type	Speed Dome
Zoom type	Optical
Operating humidity	5% RH ~ 95% RH
Operating temperature	-30°C ~ 65°C
Package Content	Quick installation guide, Adapter
Supported browsers	IE11, Chrome 57+, Firefox 52+, Safari 11
Storage humidity	5% RH ~ 95% RH
Storage temperature	-30°C ~ 70°C

Approval and Compliance	FCC (47 CFR Part 15, Subpart B); CE-EMC: (EN 55032: 2015, EN 61000-3-2: 2019, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014); UL (UL 62368-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013, IEC 62368-1:2014); CE-LVD (EN 62368-1:2014+A11:2017); BIS (IS 13252(Part 1):2010+A1:2013+A2:2015); LOA (SANS IEC60950-1 RoHS
Package Contents	Power adapter Screw Kit Screw x4 Waterproof Jacket Wall Mount Kit EcDoc QIG
Product weight (kg)	5
Dimensions (W x D x H)	220x220x353.3
Color	White
EAN	57308103101
Model Number	FCS-4072
Optical zoom	32x optical
Pan (Swivel) range	Configurable from 0.1° to 160°/s; preset speed: 240°/s , Tilt speed: configurable from 0.1° to 120°/s, preset speed 200°/s
Port Configuration	RJ45/Power /DI/Audio
Power consumption	Max 42 Watt (18 Watt for IR . 10 Watt for heater), Hi-PoE
Power supply	VAC 24V
Power supply included	Yes
Resolution	Main Stream: 50 Hz: 25 fps (2560 × 1440, 1920 × 1080, 1280 × 960, 1280 × 720) 60 Hz: 24 fps (2560 × 1440, 1920 × 1080, 1280 × 960, 1280 × 720) Sub-Stream: 50 Hz: 25 fps (704 × 576, 640 × 480, 352 × 288) 60 Hz: 24 fps (704 × 480, 640 × 480, 352 × 240) Third Stream: 50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60 Hz: 24 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240) Video Compression: Main stream: H.265+/H.265/H.264+/H.264 Sub-stream: H.265/H.264/MJPEG Third stream: H.265/H.264/MJPEG
Shutter time	1/1 s to 1/30000 s
Standard	IPv4/IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour

Storage capacity	Built-in memory card slot, support microSD/SDHC/SDXC card, up to 256 GB
Tilt range	Configurable from 0.1° to 120°/s, preset speed 200°/s
Video format	H.265/H.264/MJPEG
Weatherproof rating	IP66
Angle of view (°)	Horizontal field of view: 50.8° to 2.6° (wide-tele), Vertical field of view: 29.4° to 1.5° (wide-tele), Diagonal field of view: 57.4° to 3° (wide-tele)
Audio format	G.711alaw, G.711ulaw, G.722.1, G.726, MP2L2, AAC, PCM
Digital zoom	16
Image sensor	1/1.8" progressive scan CMOS
Indicators	Link/Act
IR cut filter	Yes
IR range	200
Lens	5.9 mm to 188.8 mm
Minimum illumination (lux)	Color: 0.005 Lux @ (F1.5, AGC ON), B/W: 0.001 Lux@ (F1.5, AGC ON), 0 Lux with IR
Mount	Wall mount

