

Slide Compound Saw

LS0714L

1 010 W • 190 mm • 6 000 min⁻¹

Light and portable saw with a laser for builders

A slide compound saw for cross and mitre cutting with a 1 010 W motor and a blade with a diameter of 190 mm. An ideal choice for construction and other demanding sectors. Four steel poles with four linear ball bearings ensure stable and accurate cutting. The laser shows the line for cutting.



Technical specifications

Capacity 90°	52 x 300 mm
Continuous Input Power	1010 W
No load speed	6000 min ⁻¹

Capacity 45°	52 x 212 mm
Capacity 45° left	40 x 300 mm
Max. Bevel Range (Left)	45 / 0 °
Max. Mitre Range (Left)	47 / 57 °
Blade Diameter	190 mm
Bore Size (Arbor Diameter)	20 mm
Power Supply Cord	2,5 m
Sound Power Level (L _{WA})	101 dB(A)

Sound Pressure Level (L _{pA})	92 dB(A)
---	----------

Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Laser Class	2

EAN 0088381062336

Link to product - www.makita.uk.com



Related products

Optional AC

122472-0

Repetitive Cut Stop



122563-7

Horizontal Vice Assembly



122571-8

Vertical Vice Assembly



122852-0

Dust bag



192621-3

Holder Set



B-29468

Circular saw blade, Specialized T.C.T,



Other

User manual

Parts drawing