



QNA-UC5G1T

Network Adapters	USB to 5GbE
PHY IC	AQC111U
I/O	1 x USB 3.2 Gen 1 Type-C; 1 x 5GbE/NBASE-T port
Transmission rates	5Gbps/2.5Gbps/1Gbps/100Mbps
Operating temperature	5 - 45 °C (23 - 113°F)
Package content	QNA- UC5G1T; 0.2M USB 3.2 Gen 1 Type-C to Type-A cable and installation guide
Port and cable	RJ-45
Note	● Windows 10, 8.1, 8, 7 requires a driver. Requires the Marvell® AQtion AQC111U driver. Click here to download the driver. ● QNAP NAS: QTS 4.3.6 (or later) is required. ● QNAP has ended official support for MacOS and Linux since 2021/01. Users can download the Marvell® AQtion AQC111U driver from Marvell®' s official website. Click here to download the driver.

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.