



95
WATT

Automatic
Voltage
Selection

2,6_{mt}
CABLE LENGTH



Main Specifications

- Compact Universal 95W Power Supply unit for Notebook and Ultrabook
- Voltage automatic selection output according to the connector used (from 12Vdc to 24Vdc)
- 10 connectors included
- Voltage input: 110-240Vac 50/60Hz
- Cable length input: 100cm
- Cable length output: 150cm
- Power: 95W Max
- Efficiency: >92%
- Overload protection
- Short circuit protection
- Internal temperature control

FULL COMPATIBILITY: 10 CONNECTORS INCLUDED

REAL SIZE.
Find your connector.

Asus/HP	Samsung	Acer/Toshiba	Asus/HP/Acer Compaq/ Fujitsu/ Toshiba/Dell/ Siemens/IBM/ Lenovo/Nec/ Packard Bell	Sony/Fujitsu	Lenovo	HP/Dell/ Compaq	HP/Compaq/ Nec/Asus	HP/Asus/Dell	Lenovo
19V-B 4x1,7mm	19V-D 5x3,4x1mm	19V-F 5,5x1,7mm	19V-G1 5,5x2,5mm	19,5V-I1 6x4,5x1,4mm	20V-M 7,9x5,6x0,9mm	19V-O 7,4x5,1x0,6mm	19V-P 4,7x1,7mm	19,5V-R 4,5x3x0,7mm	20V-S 11x4,5x0,6mm

Free extra connectors on www.tecnoware.com

If the necessary connector is not included, request it for free on www.tecnoware.com.

Specifications

Model	95W Automatic Notebook Charger
Code	FAU17610
Colour	Black
Dimensions WxHxD	11,2x4,4x2,7 cm
Dimensions with packing WxHxD	9,6x22,2x4 cm
Weight	240 g
Nominal input voltage	230 Vac
Input voltage range	110-240 Vac
Nominal input frequency	50/60 Hz
Input current Input current	0,8 A Max
Efficiency	> 92% (typical)
Connector output voltage	12Vdc, 15Vdc, 16Vdc, 18Vdc, 18,5Vdc, 19Vdc, 19,5Vdc, 20Vdc, 22Vdc, 24Vdc (selected automatically by the connector used)
Connector output current	From 7,9A to 3,9A (depending at the connector used)
Output power	95W Max
Enviromental specification	
Storage temperature	From -15 to 40 °C
Working temperature	From 0 to 40 °C
Humidity	20-80% (without condensation)
IP protection IP protection	IP20
Maximum altitude Maximum altitude	3.000 m
Certifications	CE (Safety Directive 2014/35/EU; EMC 2014/30/EU)

© 2021 Tecnoware Power Systems. The technical data may change without prior notice.

Packaging

