

Product Information

95 32 320

Cable Cutter

(ratchet principle, 3-stage)



- Sturdy. Easy to use. Stable.
- Innovative ratchet-drive.
- For cable up to Ø 60 mm
- Fixed handle with support area for putting down the pliers when cutting
- Easy handling due to low weight (825 g) and compact construction (320 mm length) - also usable in confined areas
- Cuts copper and aluminium cables up to a diameter of 60 mm (600 mm²) in one and two-handed operation
- Hardened cutting edges, precisely ground, cut smoothly and neatly without crushing
- For cutting copper and aluminium single conductors as well as multiple stranded cables
- Innovative three-stage ratchet-drive with high leverage for easy cutting in one-hand and two-hand operation
- Not suitable for steel wire, wire ropes and fine-stranded (highly flexible) conductors

| General                                          |                              |
|--------------------------------------------------|------------------------------|
| Part No.                                         | 95 32 320                    |
| EAN                                              | 4003773075172                |
| pliers                                           | black atramentized           |
| Head                                             | polished                     |
| Handles                                          | with multi-component handles |
| Weight                                           | 825 g                        |
| Dimensions                                       | 320 x 149 x 30 mm            |
| REACH compliant                                  | does not contain SVHC        |
| RoHS compliant                                   | not applicable               |
| Technical details                                |                              |
| Cutting capacity copper cable, multiple-stranded | 600 mm²                      |
| Cutting capacity copper cable, multiple-stranded | Ø 60 mm                      |
| MCM                                              | 1,200                        |

Technical changes and errors excepted

