


FCS-5212, GEMINI IP CAMERA, 6-MP, H.265, 802.3AF, POE, IR LEDS, INDOOR/OUTDOOR, TWO-WAY AUDIO

Product Images



Short Description

- 6-Megapixel resolution
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Built-in Micro SDHC/SDXC card slot for local storage
- Built-in infrared LEDs for night viewing up to 60m
- Supports 3 video streams simultaneously
- Video compression: H.264, H.265, MJPEG
- Supports 4.3X optical zoom
- Weatherproof IP67-rated housing

Description

The LevelOne FCS-5212 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP66 to operate

within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 6-Megapixel resolution and the versatility of 802.3at standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5212 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Additional Information

Harmonized System (HS) code	852589
Customs product code (TARIC)	8525890000
Features	Event: - Motion detection (human and vehicle targets classification), video tampering alarm, exception - Line crossing detection, intrusion detection - Supports human and vehicle targets classification - Face detection Privacy masks: -4 programmable polygon. Image Enhancement: - BLC, HLC, 3D DNR Image Settings: - Rotate, mirror, privacy mask, saturation, brightness, contrast, sharpness, gain
PoE Supported	Yes
2-way audio	Yes
DI/DO	Yes
IR LED for night vision	Yes
Max. Resolution	6 Megapixels
Resistance	Weatherproof, Vandalproof
IP Camera series	GEMINI
Camera Type	Bullet
Zoom type	Motorization
Operating humidity	0% RH ~ 95% RH
Operating temperature	-30°C ~ 60°C
Supported browsers	Plug-in required live view: IE 10, IE 11 Plug-in free live view : Chrome 57.0+, Firefox 52.0+ Local service: Chrome 57.0+, Firefox 52.0+
Compatible operating systems	Option accessory Mounting Kit : CAS-7303 Pole Mount CAS-7307 Corner mount CAS-7311 Junction Box CAS-7312 Power intake box
Storage humidity	0% RH ~ 95% RH
Storage temperature	-30°C ~ 70°C
Approval and Compliance	CE/FCC/UL
Compatibility	ONVIF

Package Contents	FCS-5212 Screw Kit
Product weight (kg)	1.385
Dimensions (W x D x H)	308.5x97.9x93
Color	White
EAN	4015867229569
Model Number	FCS-5212
Optical zoom	4.3 Motorized
Port Configuration	RJ-45,Power plug ,DI/DO
Power consumption	12 VDC $\pm$ 25%, 1.08 A, max. 13 W, Ø5.5 mm coaxial power plug PoE: 802.3at, Class 4, 42.5 V to 57 V, 0.36 A to 0.27 A, max. 15 W
Power supply	12 VDC $\pm$ 25%, PoE: 802.3at
Power supply included	No
Resolution	Main Stream 50 Hz: 20 fps (3200 $\times$ 1800) 25 fps (2688 $\times$ 1520, 1920 $\times$ 1080, 1280 $\times$ 720) 60 Hz: 20 fps (3200 $\times$ 1800) 30 fps (2688 $\times$ 1520, 1920 $\times$ 1080, 1280 $\times$ 720) Sub-Stream 50 Hz: 25 fps (1280 $\times$ 720, 640 $\times$ 480, 640 $\times$ 360) 60 Hz: 30 fps (1280 $\times$ 720, 640 $\times$ 480, 640 $\times$ 360) Third Stream 50 Hz: 10 fps (1920 $\times$ 1080, 1280 $\times$ 720, 640 $\times$ 480, 640 $\times$ 360) 60 Hz: 10 fps (1920 $\times$ 1080, 1280 $\times$ 720, 640 $\times$ 480, 640 $\times$ 360)
Shutter time	1/3 s to 1/100,000 s
Standard	IEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3af Power over Ethernet (PoE) TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, SRTP, SFTP
Storage capacity	Built-in memory card slot, support micro SD card, up to 256 GB
Video format	H.265/H.264/MJPEG
Weatherproof rating	IP67
Angle of view (°)	Horizontal FOV 106° to 32°, Vertical FOV 56° to 18°, Diagonal FOV 127° to 37°
Audio format	G.711/G.722.1/G.726/MP2L2/PCM

Image sensor	1/2.4" Progressive Scan CMOS
Indicators	Power Link/act
IR cut filter	Yes
IR range	60 Meters
Lens	Varifocal Motorized Lens, 2.8 to 12 mm
Minimum illumination (lux)	Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Mount	Wall mount

