Series | 4, Freestanding fridge-freezer Combination with freezer area below, 201 x 60 cm, inox look KGV39VLEA

Integrated accessories
3 x egg tray
Special accessories
KSZ10010: Snack box
KSZ10030: bottle shelf
Technical specifications
Energy efficiency class (EU 2017/1369):
E.
Average energy consumption in kilowatt hours per Year (kWh / a) (EU 2017/1369):
233
Total volume of freezer compartments (EU 2017/1369):
94
Sum of the volumes of the cold storage compartments (EU 2017/1369):
249
Airborne noise emissions (EU 2017/1369):
39
Airborne noise emission class (EU 2017/1369):
C.
Design:
Floor standing device
Decorative frame / panel:
Not possible
Device width (mm):
600
Device depth (mm):
650
Net weight (kg):
72,466
Connection value (W):
90
Protection (A):
10
Door hinge:
changeable on the right
Voltage (V):
220-240
Frequency (Hz):
50
Approval certificates:
CE, VDE
Length of connection cable (cm):
240
Storage in the event of a power failure (h):
23
Number of compressors:
1
Number of independent cooling circuits:
1
Internal fan:
no
Changeable hinges:
Yes
Number of adjustable shelves - refrigerator compartment (pcs):
2
Bottle racks:
Yes
EAN Code:
4242005197613
Brand:
Bosch
International order designation:
KGV39VLEA
Frostfree system:
no
Type of installation:
not applicable

The fridge-freezer combination with A + + and VitaFresh Box: very economical in the Consumption - holds your fruits and vegetables longer rich in vitamins and fresh.

Performance and consumption
design

- Doors : stainless steel look, side panels in Pearl Gray (VZF 07127)
- LED interior lighting in the refrigerator compartment

Comfort and security

- Electronic temperature control readable via LED
- Automatic defrost
- Super freezing

Refrigerator compartment

- 4 door racks

Fresh keeping system

- 1 VitaFresh drawer with humidity control - holds fruit and vegetables are rich in vitamins and stay fresh for longer

Freezer compartment

- LowFrost - less ice formation, faster defrosting
- 3 transparent frozen food drawers, including 1 BigBox

Dimensions

- Device dimensions (H x W x D): 201.0 cmx60.0 cmx65.0 cm

Technical information

- Door hinge on the right, changeable
- Height-adjustable feet at the front, castors at the back
- Condensate drain
- Connection value: 90 W.
- Nominal voltage: 220 - 240 V.

equipment

- 3 x egg tray
- Based on the results of the standard test over 24 hours. Actual consumption depends on the usage / location of the Device.
- So that the declared energy consumption is achieved, are to use the spacers supplied with the device. This increases the device depth by approx. 3.5 cm. The device does not use the spacers fully functional, but has a slightly higher one Power consumption.

general information

Environment and security

Assembly