

TECHNICAL DATA

|                        |                                                                                                                                                                                   |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PRODUCER               | Qoitec                                                                                                                                                                            |
| PACKAGE SIZE           | 79 x 46 x 125 mm                                                                                                                                                                  |
| USABLE POWER           | 60 W                                                                                                                                                                              |
| INPUT VOLTAGE          | 220 V - 240 V                                                                                                                                                                     |
| OUTPUT VOLTAGE         | 12 V                                                                                                                                                                              |
| OUTPUT CURRENT         | 5 A                                                                                                                                                                               |
| FREQUENCY              | 50 - 60 Hz                                                                                                                                                                        |
| AC CURRENT             | 0.71 A / 176 V                                                                                                                                                                    |
| VOLTAGE ADJUSTMENT     | 10.8 - 13.2 V                                                                                                                                                                     |
| SURGE CURRENT          | Cold start: 45 A / 230 VAC                                                                                                                                                        |
| SAFETY                 | Overload protection                                                                                                                                                               |
|                        | Overvoltage protection                                                                                                                                                            |
|                        | Short-circuit protection                                                                                                                                                          |
|                        | Overheat protection                                                                                                                                                               |
| IP RATING              | IP 45                                                                                                                                                                             |
| HOLD TIME              | 50 ms / 230 VAC                                                                                                                                                                   |
| START AND RISE TIME    | 1000 ms, 30 ms / 230 VAC                                                                                                                                                          |
| VIBRATION PROFF        | 10 - 500 Hz, 5G 10 min/cycle, X, Y, Z axes 60 min each                                                                                                                            |
| LINEAR ADJUSTMENT      | ±0.5%                                                                                                                                                                             |
| LOAD ADJUSTMENT        | ±0.5%                                                                                                                                                                             |
| R&N                    | 150 mVp-p                                                                                                                                                                         |
| ADDITIONAL INFORMATION | Aluminum housing                                                                                                                                                                  |
| ADDITIONAL INFORMATION | Switching power supply in a waterproof housing converts 230V alternating voltage into 12V DC. Made of electronic components placed on a printed circuit board in a metal housing. |
| WORKING TEMPERATURE    | -20°C ~ +60°C                                                                                                                                                                     |
| STORAGE TEMPERATURE    | -40°C ~ +80°C                                                                                                                                                                     |
| WORKING HUMIDITY       | 20 - 90%, bez kondensacji                                                                                                                                                         |
| DIMENSIONS             | 67 x 39 x 121 mm                                                                                                                                                                  |
| NET WEIGHT             | 0,2270 kg                                                                                                                                                                         |
| GROSS WEIGHT           | 0,2410 kg                                                                                                                                                                         |
| WARRANTY               | 24 months                                                                                                                                                                         |
| EAN CODE               | 5901878509495                                                                                                                                                                     |