

GENERAL FEATURES

Type	AVR
Phases (IN-OUT)	1-1
Form Factor	Tower
Power Capacity	600VA / 360W
Output Power Factor	0.60

INPUT

Input Voltage Range	180-264 VAC
Frequency Range	50Hz or 60Hz (self-adaptive)

OUTPUT

Waveform	Simulated Sine Wave
Nominal Output Voltage	230 VAC $\pm$ 8%

INPUT & OUTPUT CONNECTORS

Input Connector	CEE 7/7
Output Type	Type F
Type F (CEE 7/3)	3

TECHNICAL DETAILS

LINE Mode Efficiency [%] (Full Load)	93.8
Data Line Protection	RJ-11 Port, RJ-45 Port (100mbit)

Additional Features	Circuit Breaker Reset, AVR – Automatic Voltage Regulator
---------------------	--

COMMUNICATION

Communication	N/A
---------------	-----

Software	N/A
----------	-----

ENVIRONMENT

Noise Level	< 40dB
-------------	--------

Fan Logic	No fan
-----------	--------

Temperature	0°C – 40°C
-------------	------------

Humidity	0% – 90% RH (non-condensing)
----------	------------------------------

IP	IP 20
----	-------

LOGISTICS

Package Content	AVR, Manual
-----------------	-------------

Manual Languages	DE, SE, FI, GR, TR, BY, IT, NO, RU, UA, PL, HR, FR, HU, ES, PT, CS, CZ, KZ, EN, BG
------------------	--

EAN	4260074973556
-----	---------------

Product Dimensions (DxWxH) [mm]	161 x 166 x 87 mm
---------------------------------	-------------------

Product Weight [kg]	1.7
---------------------	-----

Package Dimensions (DxWxH) [mm]	191 x 119 x 231 mm
---------------------------------	--------------------

Package Weight [kg]	2.0
---------------------	-----

Outer Carton Dimensions	389 x 601 x 261 mm
-------------------------	--------------------

(DxWxH)

Outer Carton Weight [kg]	17.7
--------------------------	------

Pcs. per Outer Carton	9
-----------------------	---

Pcs. per Layer	36
----------------	----

Pcs. per Pallet	288
-----------------	-----

Pcs. per Pallet [Oversized]	288
--------------------------------	-----