

FCS-3406 2-Megapixel, H.265, 60fps HFR

Product Images



Short Description

- 2-Megapixel high-definition resolution
- Built-in infrared LEDs for night viewing up to 30m
- 60 fps High Frame Rate (HFR) video in 1080p
- Video compression: H.264, H.265
- Vandal-proof IK10-rated housing
- Supports 4.3X optical zoom

Description

FCS-3406 is designed for 24-hour security surveillance indoor applications; it provided an excellent quality, wide-angle & vari-focal lens, allowing plenty support of applications and wide area of coverage. Users can view the live motion image anywhere through web browser via the Internet. With the mega pixel progressive sensor and built-in IRcut filter/IR illuminator LEDs, FCS-3406 comes with 2MP/60 FPS and harp sensitivity – an idea solution for your day-and-night surveillance system.

Additional Information

Harmonized System (HS) code	852589
Customs product code (TARIC)	8525890000
Features	Motion Detection, Rotated Mode, Mirror, Color Adjustment (Brightness, Contrast, Saturation), Sharpness Adjustment, Anti-Flicker, Watermark, Privacy Mask, Automatic gain control (AGC) . Line crossing detection, up to 4 lines configurable Intrusion detection, up to 4 regions configurable Region entrance detection, up to 4 regions configurable Region exiting detection, up to 4 regions configurable Unattended baggage detection, up to 4 regions configurable Object removal detection, up to 4 regions configurable Face detection: detects faces and upload images Scene change detection, audio exception detection, defocus detection
PoE Supported	Yes
2-way audio	Yes
DI/DO	No
IR LED for night vision	Yes
Max. Resolution	2 Megapixels
Resistance	Vandalproof
IP Camera series	GEMINI
Camera Type	Dome
Zoom type	Motorization
Operating temperature	-30°C ~ 60°C
Supported browsers	IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+
Compatible operating systems	Win7/10/11
Storage temperature	0°C ~ 95°C
Approval and Compliance	CE/FCC/UL,IK10
Compatibility	ONVIF
Package Contents	FCS-3406 Screw Kit

Product weight (kg)	1,287
Dimensions (W x D x H)	133.1 x 153.4 x 153.4 mm
Color	White
EAN	4015867209097
Model Number	FCS-3406
Optical zoom	4.3 X
Port Configuration	RJ-45,
Power consumption	Without extra load: 12 VDC, 0.6 A, max. 8.0 W; PoE (802.3af, 36 V to 57 V), 0.2 A to 0.3 A, class 3
Power supply included	No
Resolution	Main Stream: 50Hz: 50fps (1920 * 1080, 1280 * 960, 1280*720) 60Hz: 60fps (1920 * 1080, 1280 * 960, 1280*720) Sub Stream: 50Hz: 25fps (704 × 576, 640 × 480) 60Hz: 30fps (704 × 480, 640 × 480) Third Stream: 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480) Fourth Stream: 50Hz: 25fps (1920 × 1080, 1280 × 720, 704 × 576, 640 × 480) 60Hz: 30fps (1920 × 1080, 1280 × 720, 704 × 480, 640 × 480) Fifth Stream 50Hz: 25fps (704 × 576, 640 × 480) 60Hz: 30fps (704 × 480, 640 × 480)
Shutter time	1 s to 1/100,000 s
Standard	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP,SNMP,IGMP, 802.1X, QoS, IPv6, Bonjour
Storage capacity	Built-in Micro SD/SDHC/SDXC slot, up to 256 GB
Video format	H.265/H.264/MJPEG
Angle of view (°)	Horizontal field of view: 103°to 38° Vertical field of view: 54°to 21° Diagonal field of view: 124°to 44°
Audio format	G.711/G.722.1/G.726/MP2L2, 64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 128 Kbps (MP2L2
Digital zoom	8x
Image sensor	1/1.8" Progressive Scan CMOS
Indicators	Power

IR cut filter	Yes
IR range	Up to 30 meter
Lens	2.8 to 12 mm motorization
Minimum illumination (lux)	Color: 0.002 Lux @ (F1.2, AGC ON), 0 Lux with IR
Mount	Ceiling mount

