


Product code: 241727 EAN: 5901583241727

LED line® E27 10W 4000K 1000lm 170-250V A60

Product description

The structural design of this product ensures effective heat dissipation. Manufacturer issues a 3-year warranty for this product. FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



The structural design of this product ensures effective heat dissipation.



Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type



Beam angle



Material (housing)



Lifespan



Number of on/off cycles



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Lamp type



Material (cover)



LED type



Power Factor




Lamp's diameter

Name of the parameter	Value
Correlated colour temperature	4000 K
Colour of the light	White
Luminous efficacy	100 lm/W
Colour rendering index Ra	80
Energy class	A+
Colour	white
Lamp's warm-up time to 60%	1
The lumen maintenance factor	96
Supply voltage range and voltage type	170-250 AC
Lamp's type	A60
Beam angle	280 °
Material (cover)	glass
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0.5
Number of on/off cycles	50000
Lamp's diameter	60
Height	110 mm
Frequency of the supply voltage	50/60Hz
For indoor use	YES
Warranty (years)	3
Flicker Free	YES
E27 fitting	E27
Luminous flux	1000 lm
Wattage	10 W
EPREL ID	632132
Date of first placement on the market	2017-03-01


Name of the parameter	Value
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Total luminous flux (EPREL)	1000
Is this product a light source? (EPREL)	Yes
Beam angle in degrees (EPREL)	280
On-mode power P _{on} (EPREL)	10
Networked standby power P _{net} (EPREL)	0
Lifetime L70B50	30000
Connected light source (EPREL)	No
Useful luminous flux Φ _{use} (EPREL)	1000
Non-directional or directional light source (EPREL)	NDLS
Mains or non- mains light source (EPREL)	MLS
Colour-tuneable light source (EPREL)	No
Chromaticity coordinates x i y (EPREL)	0.38 0.377
Dimmable function	No
Peak luminous intensity (EPREL)	— cd
R9 colour rendering index value (EPREL)	4
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Flicker metric P _{stLM}	1
Standby power P _{sb}	0
Stroboscopic effect metric SVM	0.4
Form of the product (EPREL)	—
Energy efficiency class 2019/2015	F
Minimum purchase quantity	—
Colour consistency in McAdam ellipses	≤6
Displacement factor D _f	0.5
Contain icon	—

Pre-packaging




Width [mm]	65
Height [mm]	127
Length [mm]	65
Weight [kg]	0,75

Cumulative packaging



Number of pieces	100
Width [mm]	340
Height [mm]	275
Length [mm]	665
Weight [kg]	8,5
Volume [m3]	0,0621775

Europallet



Number of pieces	1500
Bulk quantity	15
Weight [kg]	127,5
Weight [kg]	127,5
Pallet height [mm]	1519
Quantity in 1 layer	3
Number of layers	5