



Product data sheet

Power tools for trade & industry

Cordless Screwdriver

GSR 12V-35 HX



The ideal combination of compactness, productivity and performance

The most important data

Torque (soft/hard/max.)	20/35/- Nm
No-load speed (1st gear / 2nd gear)	0 – 460 / 0 – 1,750 rpm
Max. screw diameter	8 mm

Part Number 0 601 9J9 103

[> More product information](#)

Technical data

Technical data

Torque (soft/hard/max.)	20/35/- Nm
No-load speed (1st gear / 2nd gear)	0 – 460 / 0 – 1,750 rpm
Battery type	Lithium-ion
Chuck capacity, min./max.	0.8 / 10 mm
Battery voltage	12.0 V
Weight excl. battery	0.57 kg
Torque settings	20+1
Tool dimensions (height)	160 mm
Packaging dimensions (width x length x height)	234 x 342 x 108 mm
Drill chuck, version	1/4" with internal hexagon shank
Clamping range, min.	0.8 mm
Clamping range, max.	10 mm

'Total vibration values (Drilling in metal)'

Vibration emission value ah	0 m/s ²
Uncertainty K	1.5 m/s ²

'Total vibration values (Screwdriving)'

Vibration emission value ah	0 m/s ²
Uncertainty K	1.5 m/s ²

Drilling diameter

Max. drilling diameter in wood	32 mm
Max. drilling diameter in steel	10 mm

Screw diameter

Max. screw diameter	8 mm
---------------------	------

Noise/vibration information

Drilling in metal

Vibration emission value ah	0 m/s ²
Uncertainty K	1.5 m/s ²

Screwdriving

Vibration emission value ah	0 m/s ²
Uncertainty K	1.5 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Highly compact cordless screwdriver in the 12V class enables easy access to tight and narrow spaces
- With up to 1,750 rpm, the GSR 12V-35 HX is the fastest 2-gear cordless screwdriver in the 12V category
- Lockable 1/4" bit interface for easy bit exchange

