

FCS-5201 GEMINI Fixed IP Camera, 2-MP, H.265

Product Images



Short Description

- Built-in infrared LEDs for night viewing up to 30m
- Removable IR-cut filter for day and night surveillance
- 2-Megapixel (1920 x 1080) high-definition resolution
- Video compression: H.264, H.265, MJPEG
- Supports IPv4/IPv6 network operation

Description

The LevelOne FCS-5201 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5201 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Fast Ethernet RJ45	RJ-45, 10/100 Mbps Ethernet,PoE
Harmonized System (HS) code	852589
Customs product code (TARIC)	8525890000
Features	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark
PoE Supported	Yes
2-way audio	No
DI/DO	No
IR LED for night vision	Yes
Max. Resolution	2 Megapixels
Resistance	Weatherproof
IP Camera series	GEMINI
Camera Type	Bullet
Zoom type	Fixed
Operating humidity	0% RH ~ 95% RH
Operating temperature	-30°C ~ 50°C
Supported browsers	IIE7+, Chrome18-42, Firefox5.0+, Safari5.02+
Approval and Compliance	CE/FCC,IP67 TVS 2000V lightning protection, surge protection and voltage transient protection
Compatibility	Option accessory Mounting Kit : CAS-7303 Pole Mount CAS-7307 Corner mount CAS-7311 Junction Box
Package Contents	FCS-5201 Quick Installation Guide Resource CD (User Manual, Utility, QIG)
Product weight (kg)	0,28
Dimensions (W x D x H)	69.1 x 66 x 172.7 mm
Color	White
EAN	4015867207734

Model Number	FCS-5201
Power consumption	12 VDC, 0.4 A, Max: 5 W PoE: (802.3af, 37 V to 57 V), 0.2 A to 0.13 A, Max: 7 W
Power supply	VDC12V/1A,PoE 802.3af
Power supply included	No
Resolution	1920 * 1080
Shutter time	1/3 s to 1/100, 000 s, support slow shutter
Standard	IEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3af Power over Ethernet (PoE) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS
Video format	H.265/H.264/MJPEG
Weatherproof rating	IP67
Angle of view (°)	83.6
Digital zoom	8x
Image sensor	1/2.8" progressive scan CMOS
Indicators	Power
IR cut filter	Yes
IR range	Up to 30 meter
Lens	Board lens, Fixed-focal, f=4mm, F2.0
Minimum illumination (lux)	1/3s to 1/100, 000s

