



- Supports the NVIDIA GeForce RTX™ 30 Series GPUs
- Full modular cable design
- Flat cable equipment
- 10-year warranty
- 80 Plus Gold certified for high efficiency
- 100% all Japanese 105oC capacitor
- Active PFC design
- Industrial level protection with OVP,OCP,OPP,OTP, SCP,UVP
- LLC Half Bridge Topology with DC-DC module design

SPECIFICATIONS

Product Name	MPG A750GF
Form Factor	ATX
Rated Wattage	750W
Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (fully modular)
Fan Size	140 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	150 x 160 x 86 mm
PFC Type	Active PFC
Input Voltage Range	100~240 VAC
Input Frequency Range	47~63 Hz
Protection	OCP / OVP / OPP / OTP / SCP / UVP
ATX (24 pin)	1
EPS (8 pin)	2
PCI-E (6+2 pin)	6
SATA (15 pin)	8
MOLEX (4 pin)	4
FDD (4 pin)	1

MPG A750GF

MPG A750GF								
AC INPUT		100-240~,10A,47~63Hz						
DC OUTPUT	+5V +3V +12VMBPH +12VCPU +12VVGA1 +12VVGA2 -12V +5Vsb							
	22A	22A	25A	25A	35A	35A	0.3A	2.5A
TOTAL POWER	120W		750W					
	750W							

CONNECTOR					
ATX (20+4 PIN)	EPS (4+4 PIN)	PCI-E (6+2 PIN)	SATA	MOLEX (PERIPHERAL)	FDD
1	2	6	8	4	1