

SCART to HDMI Converter

Quick Installation Guide Ver. 1.0

All brand names and trademarks are properties of their respective owners

Thank you for choosing our products. We focus on producing professional, high-quality, cost-effective high-tech products, So you can easily enjoy high-definition digital life brought by technology. For the optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting the product. And please keep this manual for future reference.

INTRODUCTION:

This SCART To HDMI converter is a universal converter for analog SCART input to HDMI 1080p (60HZ) output. It can connect the playback device only has SCART interface such as DVD , Set-top box to the HD display device. The analog to digital conversion in this module employs 10 bits maximal 162MSPS sampling, black/white level expansion, color transition improvement, dynamic range expansion, blue stretch, auto-detect and auto-convert the composite signal to 1080p(60Hz) output. Making video come alive, delivering the sharpest, most realistic HD visuals.

FEATURES:

- No need to install drivers, portable, flexible, plug and play.
- Provide advanced signal processing to ensure great precision, colors, resolutions, and details.
- Support PAL, NTSC3.58, NTSC4.43, SECAM, PAL/M, PAL/N standard TV formats input.
- Support HDMI 1080p or 720p output.


PACKAGE CONTENTS:

- 1xSCART to HDMI Converter
- 1xUSB cable
- 1xUser Manual


1

2

OPERATION CONTROLS AND FUNCTIONS:



- ① SCART : SCART Input Interface. Use a SCART to SCART cable to connect your SCART device to this converter. Such like DVD, Sky Box, STB, etc.



- ① 1080P/720P : Output video resolution switch button.
② HDMI Output : Use a HDMI to HDMI cable to connect this converter to your TV which has a HDMI input interface.
③ Power : When the DC5V power on, this indicator will be light.
④ DC/5V : Connect to power adapter or use the USB power cable to connect the converter to the computer's USB, TV's USB or your 5V USB charger, etc.

CONNECTION DIAGRAM:



3

SPECIFICATIONS:

SCART Input	PAL, NTSC3.58, NTSC4.43, SECAM, PAL/M, PAL/N
HDMI Output	1080p/720p
HDMI Output Cable Distance	≤7m AWG26 HDMI Standard Cable
SCART Input Cable Distance	≤8m AWG26 SCART Standard Cable
Max Working Current	350mA
Power Adapter Format	AC 100V-240V 50/60HZ, DC 5V/1A
Operating Temperature Range	-10~+55°C
Storage Temperature Range	-20~+60°C
Operating Humidity Range	10~90%RH (No Condensation)
Storage Humidity Range	5~95%RH (No Condensation)
Case Dimension	88.5X57.5X25 (mm)
Weight	60g

- Note : Please correctly use and keep the converter to guarantee the product performance and work as expected.
- 1.Please do not expose this unit to the damp, high-temperature, dusty, erosive, or oxidative environment.
 - 2.All parts will be free from the strong shake, hit, fall.
 - 3.Please do not touch the item with wet hands.
 - 4.Please hold the plug when unplugging. Do not pull the power cable directly.
 - 5.Please turn the unit off when it is not in use for a long period of time.
 - 6.Please do not open the cover and do not touch the inside parts.
 - 7.Please use the original factory power adapter.

4