TOURING 18



ELEMENTS Tronic 12V 24V

Wet Gel MF AGM

Pb-Ca EFB

230V

- Battery charger with TRONIC technology for WET, GEL, Pb-Ca, AGM, MF, EFB 12/24 V batteries.
- Battery charge status LED signal. Key to set the voltage (12 and 24 V).
- Protection against overcharging, pole inversion and recognition of charge voltage.
- Light and compact: only 3.4 kg.

TECHNICAL DATA

CODE	**807593**	CHARGING VOLTAGE	**12 / 24 V**	MAX.RATED REFERENCE CAPAC.	**180 / 115 Ah**
SINGLEPHASE MAINS VOLTAGE	**230 V**	EFFECTIVE CHARGING CURRENT	**15 / 8 A**	DIMENSIONS (LxWxH)	**10 x 19 x 19 cm**
MAINS FREQUENCY	**50 / 60 Hz**	RATED CHAR.CUR.EN60335-2-29	**9 / 6 A**	WEIGHT	**3,440 kg**
CHARGING ABSORBED POWER	**230 W**	MIN.RATED REFERENCE CAPAC.	**60 / 50 Ah**		

ON REQUEST ACCESSORIES

BATTERY CHARGERS FUSES	
802256	FUSES 15A 10 PCS

DESCRIPTION

Battery charger with electronic control of the charging steps, automatic interruption and restart (TRONIC), for charging WET, GEL, Pb-Ca, AGM, MF, EFB batteries with 12V/24V voltage.
With warning LED to indicate battery charge status.
Fit with protection against overloads and polarity reversal and recognition of battery voltage.

DOWNLOAD

CATALOG IMAGE

INSTRUCTION MANUAL

CERTIFICATE

USEFUL LINKS

VIDEO