

	SKY JET	SKY JET	SKY JET	NEW SKY JET	NEW SKY JET	NEW SKY JET
Picture just for reference						
Model name	1S	4S	3S	NITRO 16	NITRO PRO	NITRO
Motor	250W	250W	250W	250W	250W	250W
Battery	36V 7.5AH	36V 10AH	36V 10AH	36V8AH	36V10AH	36V10AH
FRAME	16" STEEL	20" ALLOY	20" ALLOY	Steel	Steel	Steel
Size of Frame	380 MM	400MM	420MM	16 inch	20 inch	20 inch
Top speed	25KM/H	25KM/H	25KM/H	25KM/H	25KM/H	25KM/H
Range	35-45KM	45-60KM	45-60KM	25-30km	45 - 60 km	45 - 60 km
Charging time	3-4H	3-5 H	3-5 H	6 hours(first time)	6 hours(first time)	6 hours(first time)
Wheel	16" ALLOY WHEEL	20"ALLOY WHEEL	20"ALLOY WHEEL	16"1.95	20"4.0	20"4.0
Crankset	S03-3148P24PS, ALLOY CRANK, 1/2"3/32"46T*165L	PROWHEEL PRO-546PP-3,ALLOY CRANK, 1/2"3/32"46T*165L	PROWHEEL PRO-546PP-3,ALLOY CRANK, 1/2"3/32"46T*165L	140*48T	152*40T	152*40T
Shifter Right	NIL	SHIMANO ASLTX50R7CT, PLASTIC,7SP	SHIMANO ASLTX50R7CT, PLASTIC,7SP	NIL	NIL	NIL
Front derailleur	NIL	WITHOUT	WITHOUT	NIL	Shimano	Shimano
Rim	INCLUDED IN ALLOY WHEEL	INCLUDED IN ALLOY WHEEL	INCLUDED IN ALLOY WHEEL	Magnesium 16 inch	Magnesium 20 inch	Magnesium 20 inch
Front tire	16"1.95", KENDA	20X4.0" KENDA	20X4.0",CST OR KENDA	16"1.95	20"4.0	20"4.0
Rear tire	16"1.95", KENDA	20X4.0" KENDA	20X4.0",CST OR KENDA	16"1.95	20"4.0	20"4.0
Front brake	MECHANIC DISC BRAKE	MECHANIC DISC BRAKE	MECHANIC DISC BRAKE	Disc brake	Disc brake	Disc brake
Rear bake	MECHANIC DISC BRAKE	MECHANIC DISC BRAKE	MECHANIC DISC BRAKE	Disc brake	Disc brake	Disc brake
Display	C5,LCD	C6,LCD	ID4,LCD	LCD 61C	LCD 61F	LCD 61F
Saddle	COMFORTABLE SPORT	SELLE ROYAL LOOKIN	COMFORTABLE SPORT	Skyjet logo	Skyjet logo	Skyjet logo
Freewheel	KDF-12,1/2"1/8"16T,1SP	SHIMANO AMFTZ5007428,STEEL,7SP	SHIMANO AMFTZ5007428,STEEL, 7SP	NIL	Shimano-6-speed	Shimano-6-speed
Chain	KMC,S1	KMC Z7	KMC Z7	98 pieces	120 pieces	120 pieces
Fender	PP	STEEL	PP	Plastic fenders	Plastic fenders	Plastic fenders
Front fork	RIGID,STEEL	Suspension fork,ALLOY CROWN,STEEL LEG,WITH LOCK-OUT	Suspension fork,ALLOY CROWN,STEEL LEG,WITH LOCK-OUT	Suspension fork	Suspension fork	Suspension fork
Front light	LED,36V Controlled By Display	36V Controlled By Display	LED,36V Controlled By Display	LED	LED	LED
Rear light	BATTERY LIGHT	BATTERY LIGHT	BATTERY LIGHT	NIL	LED	LED
Rear derailleur	NIL	SHIMANO RD-TY3000,7SP	SHIMANO RD-TY3000,7SP	NIL	Shimano-6-speed	Shimano-6-speed
Handlebar	Alloy	Alloy	Alloy	Aluminum	Aluminum	Aluminum
Distance of Handlebar	W: 600MM	W: 580MM	W: 580MM	54CM	54CM	54CM
Stem	Folding type, Steel	Folding type,Alloy	Folding type,Alloy	Steel	Steel	Steel
Seat post	ALLOY	Alloy	STEEL	Steel	Steel	Steel
High of Seat Post	250MM	400MM	350MM	30CM	25CM	25CM
SHORK	SPRING PRESSURE	WITHOUT	WITHOUT	NIL	NIL	NIL
NET WEIGHT INC BATTERY	20.8KGS	32.2KGS	30.8KGS	18KG	28KG	28KG
BATTERY NET WEIGHT	2.0KGS	3.0KGS	3.0KGS	2.2	2.7	2.7
Permissible maximum loading capacity	100KG	120KG	120KG	100KG	110KG	110KG