

broad	90 cm
case color	stainless steel
installation	Integrable
air circulation	Exhaust air, circulating air (special accessories available separately)
overall fan performance	140W
controls	7-segment display, short-stroke keys
Regulation of power levels	3-stage + 2 intensive
Max. fan output extract air	395 m³/h
Blower output in intensive level exhaust air mode	700 m³/h
Volume at maximum speed (2010/30/EC)	53dB
Volume boosted (2010/30/EC)	69dB
Max. fan power recirculation	358 m³/h
Blower output for intensive level recirculation mode	641 m³/h
Material of the grease	Washable stainless steel

filter	
energy efficiency class	B
Estimated annual electricity consumption	38.8 kWh/year

Dimensions

height	426-426/426-426mm
broad	898mm
device depth	290mm
Minimum distance to electric hob	430mm
Minimum distance to the gas hob	650mm
Diameter of the exhaust air socket	120 / 150mm
backflow flap	no
Length of power cord	175 cm
net weight	13.1kg
Device height exhaust air max	426mm
Device height exhaust air min	426mm

Device height circulating air max	426mm
Device height circulating air min	426mm
Niche width minimal	524mm
Maximum niche width	524mm
niche depth	290mm

Comfort

air quality sensor	no
Hood control via hob	no
iQdrive	Yes
Extremely quiet	Yes
intensive level	Yes
Delay shut off modes	10 mins
remote control	no

lighting

type of lamps	LEDs
Number of lamps (pcs)	3

total power of the lamps	6 w
total light intensity	355 lux
Lighting type soft light	Yes
Average illuminance of the lighting system on the cooking surface E _{middle} (2009/125/EC)	355 lux
Adjustable color temperature of the working light via Home Connect	no
emotionLight Pro	no

Networking

Home Connect	no
--------------	----
