

DIGITUS Conjunto de cabo de interconexões CAT 5e SF/UTP

DK-1532-020
EAN 4016032199663



CAT 5e SF-UTP patch cord, PVC AWG 26/7, length 2 m, color grey

The DIGITUS® Category 5e Class D patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 5e specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 5e cabling. The performance is tested up to 100 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 5e, because of the transparent blue colored connector.

Melhor desempenho e melhor qualidade de ligação com a rede.

- 2x Conectores RJ45 (8P8C)
- Coberturas com proteção contra dobras, redução de tensão e proteção contra alavanca de retenção
- Indicação de comprimento nas tampas
- Assortment: Twisted Pair Patch Cables
- Slim Version: no
- Length: 2 m
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Category: CAT 5e
- Packaging: DIGITUS Polybag
- Color: grey
- Configuration: 1:1
- Jacket: PVC
- Shielding: SF-UTP, foil and braid shielding
- Structure: 4 x 2 AWG 26/7, twisted pair

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	150	9.70	46.00	33.00	28.00	42,504.00
Packaging Unit Inside	10	0.65	7.50	25.00	42.00	7,875.00
Packaging Unit Single	1	0.06	1.50	14.00	25.00	525.00
Net single without Packaging	1	0.06	1.50	14.00	25.00	525.00