



Bevel brush crimped KBU dia. 125x10 mm M14 steel wire dia. 0.35 mm angle grinders

**Bevel brush crimped KBU dia. 125x10 mm M14 steel wire
dia. 0.35 mm angle grinders**

Item number: [43220120](#)

EAN: [4007220104736](#)

Excellent for medium-duty brushing such as deburring, cleaning and derusting.

Steel wire is the most common filament material. Brushes with steel wire as the filament material are especially well-suited to work on surfaces and deburring. PFERD TOOLS special wire has high tensile strength and bending fatigue strength. This ensures that the wire wears down in the optimal way, as well as a long tool life, even in extreme brushing applications.

Steel wire withstands temperatures up to 300 Å°C.

Technical information

Dia. external	125 mm
Dia. filament material	0.35 mm
Dia. thread	M14x2
Filament material	Steel wire (ST)
Length, filament	22 mm
Max. RPM	11000 RPM
Mounting system	Thread
Packaging	Industrial packaging
RPM, optimum	6.300 - 11.000 RPM
Width	10 mm

Advantages

- ✓ Optimal access to hard-to-reach areas such as inner edges, grooves and keyways.
 - ✓ Highly flexible, enabling optimal adjustment to the workpiece contour.
 - ✓ Suitable for use on angle grinders up to 80 m/s.
 - ✓ Long tool life through use of PFERD TOOLS special wire.
 - ✓ Creates fine surfaces.
-

Recommendations for use

- ✓ Please observe the recommended rotational speeds.
 - ✓ For optimum results, use on speed-adjustable angle grinders.
-

Materials that can be worked

- ✓ Cast iron
 - ✓ Cast steel
 - ✓ Elastomers
 - ✓ Steel, cast steel
 - ✓ Steel materials with a hardness > 54 HRC
 - ✓ Steels up to 1,200 N/mm² (< 38 HRC)
 - ✓ Wood
-

Applications

- ✓ Cleaning
 - ✓ Deburring
 - ✓ Derusting
 - ✓ Paint stripping
 - ✓ Removing oxide layers
 - ✓ Roughening
-

Drive types

- ✓ Angle grinder
 - ✓ Cordless angle grinder
-

**PFERD
TOOLS**



August Rüggeberg GmbH & Co. KG
Hauptstraße 13
51709 Marienheide

+49 2264 9-0

+49 2264 9-400

info@pferd.com