



|                |                       |                    |               |
|----------------|-----------------------|--------------------|---------------|
| Power          | <b>20 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux* | <b>2050 lm (120°)</b> | Colour temperature | <b>6000 K</b> |
| Light colour   | <b>CW</b>             | Beam angle         | <b>100 °</b>  |
| IK             | <b>07</b>             | Protection class   | <b>IP65</b>   |



See more on dedicated page 





 Declaration of Conformity



 Photometric file

#### Technical data:

|                              |                 |
|------------------------------|-----------------|
| Product code                 | SLI029053CW_PW  |
| Power                        | 20 W            |
| Nominal current              | 90 mA           |
| Voltage                      | 230 V           |
| Energy consumption           | 20 kWh/1000h    |
| Frequency                    | 50HZ Hz         |
| Protection class             | I               |
| Power supply included        | +               |
| Power factor                 | 0.9             |
| Useful luminous flux*        | 2050 lm (120°)  |
| Luminous flux**              | 2050 lm (360°)  |
| Light efficiency             | 103 lm/W        |
| Colour temperature           | 6000 K          |
| Light colour                 | CW              |
| Beam angle                   | 100 °           |
| RA                           | >70             |
| Uniformity of color SDCM max | 5               |
| Dimmable                     | No              |
| Working temperature range    | -20/+40 °       |
| Lifespan                     | 17000 h         |
| Housing material             | Aluminum, GLASS |
| IK                           | 07              |
| Protection class             | IP65            |
| Colour                       | White           |
| Dimension (axbxc)            | 120x90x27 mm    |
| For use                      | Outside         |
| Assembly method              | On the ceiling  |
| Application                  | EXT             |
| Made in                      | PRC             |



\*Applies to the LED source used. \*\*Luminaire luminous flux