

FCS-5096 GEMINI Zoom IP Camera, 2-MP H.265, 60FPS, 802.3AF, POE, IR LEDs, INDOOR/OUTDOOR, TWO-WAY AUDIO

Product Images



Short Description

- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- P-iris automatic lighting control for high image quality
- Built-in infrared LEDs for night viewing up to 50m
- 60 fps High Frame Rate (HFR) video in 1080p
- Video compression: H.264, H.265
- Vandal-proof IK10-rated housing
- Weatherproof IP67-rated housing
- Supports 4.3X optical zoom

Description

The LevelOne FCS-5096 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5096 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Additional Information

Fast Ethernet RJ45	RJ45 PoE
Terminal block	DI/DO
Harmonized System (HS) code	852589
Customs product code (TARIC)	8525890000
Features	Motion Detection, Rotated Mode, Mirror, Color Adjustment (Brightness, Contrast, Saturation), Sharpness Adjustment, Anti-Flicker, Watermark, Privacy Mask, Automatic gain control (AGC) .
PoE Supported	Yes
2-way audio	Yes
DI/DO	Yes
IR LED for night vision	Yes
Max. Resolution	2 Megapixels
Resistance	Weatherproof
IP Camera series	GEMINI
Camera Type	Bullet
Zoom type	Motorization
Operating temperature	-30°C ~ 60°C
Supported browsers	Plug-in required live view: IE8+, Chrome 41.0-44, Firefox 30.0-51, Safari 8.0-11 Plug-in free live view: Chrome 45.0+, Firefox 52.0+
Storage temperature	0°C ~ 95°C
Approval and Compliance	CE,FCC,UL,IK10,IP67
Compatibility	ONVIF,ISAPI. Ooption accessory Mounting Kit : CAS-7303 Pole Mount CAS-7307 Corner mount CAS-7311 Junction Box CAS-7312 Power intake box
Package Contents	FCS-5096 Screw Kit Quick Installation Guide Resource CD (User Manual, Utility, QIG)
Product weight (kg)	1,893
Dimensions (W x D x H)	332.73 x 332.73 x 144.13 mm

Color	White
EAN	4015867205334
Model Number	FCS-5096
Optical zoom	4.3X
Power consumption	12 VDC, 1.3A, max. 15.5W PoE (802.3at, 42.5V to 57V), 0.5A to 0.1A, max. 17.5W
Power supply	VDC12V/1A,PoE 802.3at
Power supply included	No
Resolution	50Hz: 50fps (1920 * 1080, 1280 * 960, 1280*720) 60Hz: 60fps (1920 * 1080, 1280 * 960, 1280*720)
Shutter time	1/3 s to 1/100,000 s
Standard	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP,IGMP, 802.1X, QoS, IPv6, Bonjour
Storage capacity	Built-in microSD/SDHC/SDXC slot, up to 128 GB
Video format	H.265/H.264/MJPEG
Weatherproof rating	IP67
Angle of view (°)	Horizontal field of view: 105 to 35 Vertical field of view: 56 to 20 Diagonal field of view: 126 to 40.5
Audio format	G722.1/G711ulaw/G711alaw/G726/MP2L2/PCM
Image sensor	1/2.8" Progressive Scan CMOS
Indicators	Power
IR cut filter	Yes
IR range	Up to 50 meter
Lens	2.8 to 12 mm
Minimum illumination (lux)	Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR B/W: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR

