

UniFi<sup>®</sup> SWITCH



# UniFi Switch Lite 8 PoE

The USW-Lite-8-PoE is a fully managed Layer 2 switch with eight Gigabit Ethernet ports for your RJ45 Ethernet devices. Four ports also offer auto-sensing 802.3at PoE+ that provide up to a total PoE wattage of 52W for UniFi Access Points or other PoE devices. Managed and configured by the UniFi Network Controller with UniFi mobile app support, the USW-Lite-8-PoE offers Layer 2 switching protocols and features. The UniFi Network Controller and mobile app allow admins to configure and monitor virtually all of the switch features in a graphical user interface from anywhere.



## Mechanical

|            |                                              |
|------------|----------------------------------------------|
| Dimensions | 99.6 x 163.7 x 31.7 mm (3.92 x 6.44 x 1.25") |
| Weight     | 450 g (15.87 oz)                             |

## Hardware

|                                   |                                              |
|-----------------------------------|----------------------------------------------|
| Total Non-Blocking Line Rate      | 8 Gbps                                       |
| Max. Power Consumption            | 8W                                           |
| Power Method                      | 54VDC, 1.1A Power Adapter                    |
| Power Supply                      | External 54V/60W Power Adapter               |
| Supported Voltage Range           | DC 50V to 57V                                |
| Networking Interfaces             | (8) 10/100/1000 Mbps Ethernet RJ45 Ports     |
| PoE Interfaces                    | (4) PoE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-) |
| Management Interface              | Ethernet In-Band                             |
| Max. PoE+ Wattage per Port by PSE | 30W                                          |
| Modes                             | SMB Layer 2 PoE Gigabit Ethernet Switch      |
| Operating Temperature             | -15 to 40° C (5 to 104° F)                   |
| Operating Humidity                | 10 - 90% Noncondensing                       |
| Certifications                    | CE, FCC, IC                                  |

## LEDs

|          |                                                                                                                                                                                         |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| System   | (1) Power, Blue/White<br>Flashing White: Bootup in Progress<br>Flashing Blue: Firmware Upgrading<br>Steady White: Factory Defaults, Awaiting Adoption<br>Steady Blue: Device is Adopted |
| Ethernet | Green: 1G, Amber: 10/100 Mbps                                                                                                                                                           |
| PoE      | Amber: IEEE 802.3af/at                                                                                                                                                                  |



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at: [www.ui.com/support/warranty](http://www.ui.com/support/warranty)  
©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, and UniFi are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.