

## Philips V Line LCD monitor with SmartControl Lite 223V5LSB2/10

**Brand :** Philips

**Product family:** V Line

**Product code:** 223V5LSB2/10

**Product name :** LCD monitor with SmartControl Lite 223V5LSB2/10

- V Line  
- 21.5" (54.6 cm)  
V Line LCD monitor with SmartControl Lite

Philips V Line LCD monitor with SmartControl Lite 223V5LSB2/10:

Enjoy vivid LED pictures on this Philips display. Equipped with SmartControl Lite, it's a great choice! Philips V Line LCD monitor with SmartControl Lite 223V5LSB2/10. Display diagonal: 54.6 cm (21.5"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED. Display: LED. Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 90°, Viewing angle, vertical: 65°. VESA mounting. Product colour: Black



Display		Ergonomics	
Display diagonal *	54.6 cm (21.5")	Picture-in-Picture	✗
Display brightness (typical)	200 cd/m <sup>2</sup>	On Screen Display (OSD)	✓
Display resolution *	1920 x 1080 pixels	On Screen Display (OSD) languages	Simplified Chinese, Czech, German, Dutch, English, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Turkish, Ukrainian
Native aspect ratio *	16:9	Number of OSD languages	18
Response time	5 ms	Plug and Play	✓
HD type *	Full HD	LED indicators	Operation, Stand-by
Display technology *	LED	Thin Client	
Backlight type	W-LED	Thin client installed	✗
Screen shape *	Flat	Power	
Supported graphics resolutions	1920 x 1080 (HD 1080)	Energy efficiency class (SDR) *	E
Aspect ratio	16:9	Energy consumption (SDR) per 1000 hours *	16 kWh
Contrast ratio (typical) *	600:1	Power consumption (typical) *	15.61 W
Contrast ratio (dynamic)	10000000:1	Power consumption (standby) *	0.5 W
Viewing angle, horizontal	90°	Power consumption (off)	0.5 W
Viewing angle, vertical	65°	AC input voltage	100 - 240 V
Display number of colours *	16.78 million colours	AC input frequency	50/60 Hz
3D	✗	Energy efficiency scale	A to G
Panel type *	TFT/S-PVA	Network	
Pixel pitch	0.248 x 0.248 mm	Wi-Fi	✗
Horizontal scan range	30 - 83 kHz	Bluetooth	✗
Vertical scan range	56 - 76 Hz	Operational conditions	
Viewable size, horizontal	47.7 cm	Operating temperature (T-T)	0 - 40 °C
Viewable size, vertical	26.8 cm	Storage temperature (T-T)	-20 - 60 °C
Digital horizontal frequency	30 - 83 kHz	Operating relative humidity (H-H)	20 - 80%
Digital vertical frequency	56 - 76 Hz	Relative humidity	20 - 80%
Separate H/V sync	✓	Operating altitude	0 - 3658 m
Sync-on-green (SOG)	✓		
RGB colour space	sRGB		
Performance			
NVIDIA G-SYNC *	✗		
Component video sync	Separate sync		

<b>Performance</b>		<b>Operational conditions</b>	
Windows operating systems supported	✓	Non-operating altitude	0 - 12192 m
Mac operating systems supported	✓	<b>Sustainability</b>	
Flicker-free technology	✓	Sustainability certificates	EPEAT Silver, ENERGY STAR
<b>Multimedia</b>		<b>Weight &amp; dimensions</b>	
Built-in speaker(s) *	✗	Width (with stand)	503 mm
Built-in camera *	✗	Depth (with stand)	213 mm
<b>Design</b>		Height (with stand)	376 mm
Market positioning *	Home	Weight (with stand)	2.61 kg
Product colour *	Black	Width (without stand)	50.3 cm
Feet colour	Black	Depth (without stand)	5 cm
Certification	BSMI, CE Mark, FCC Class B, GOST, PSB, SASO, SEMKO, TUV/ISO9241-307, cETLus, WEEE	Height (without stand)	31.6 cm
	BSMI, CE Mark, FCC Class B, GOST, PSB, SASO, SEMKO, TUV/ISO9241-307, cETLus, WEEE	Weight (without stand)	2.35 kg
Compliance industry standards	BSMI, CE Mark, FCC Class B, GOST, PSB, SASO, SEMKO, TUV/ISO9241-307, cETLus, WEEE	<b>Packaging data</b>	
<b>Ports &amp; interfaces</b>		Stand included	✓
Built-in USB hub *	✗	Package width	555 mm
VGA (D-Sub) ports quantity	1	Package depth	107 mm
DVI port	✗	Package height	414 mm
Audio input	✗	Package weight	3.87 kg
Headphone out *	✗	<b>Other features</b>	
<b>Ergonomics</b>		Display	LED
Panel mounting interface	100 x 100 mm	On/off switch	✓
Cable lock slot *	✓	Built-in subwoofer	✗
Cable lock slot type	Kensington	TV tuner integrated	✗
VESA mounting *	✓	Recommended resolution	1920 x 1080 @ 60 Hz
Tiltable	✓	Manual	✓
Tilt angle range	-5 - 20°	Recyclable packaging material	100%
		Energy efficiency class (old)	E
		Mean time between failures (MTBF)	30000 h
		Ethernet LAN	✗



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.