

		FF4403MXZH
Description	Remarks	50X50
Source	Gas (NG-LPG) / Elc	Gas (NG-LPG)/ Elc
Down Cavity Volume	Liter (lt)	52lt
Oven Size	W*D*H (mm)	500*594*796
Packaging Size	Styrofoam Packaging W*D*H (mm)	540*670*880
Loading Quantities	40' HC	224
Top Table	Color (Painted / Stainless Steel)	Stainless Steel
Control Panel	Color (Painted / Stainless Steel)	Stainless Steel
Bottom Fascia	Color (Painted / Stainless Steel)	Stainless Steel
Side Panels	Color (Painted / Stainless Steel)	Grey painted
Function		
Timer for Cooktop	Mechanical (reminding or cut off function)	X
Electric Ignition (cooktop)	Automatic / Push Button	X
Electric Ignition (oven)	Automatic / Push Button	X
Oven Light (inner lamp) Down Cavity	15/25W	X
Cooktop		
Top Cover	Material of top cover	Metal Top Lid
Cover Color		Grey painted
Burner / Hotplate Type		4 Multigas
Flame Failure Device(FFSD)	Safety (Thermocouple)	√
Cooktop (HOB) Material	Enamelled/Inox	Inox
Burners & Heating Elements (Dimensions & Powers)		
Rapid Gas Burners	Dimensions(mm) & Qty	ø100mm * 1
Semi Rapid Gas Burners		ø75mm * 2
Auxiliary Gas Burners		ø55mm * 1
Triple Crown Gas Burners		X
Hi-Lite 140mm		X
Hi-Lite 180mm		X
Booster 160mm		X
Booster 180mm		X
Hot Plate 145mm		X
Hot Plate 145mm(Rapid)		X
Hot Plate 180mm		X
Rapid Gas Burners	Powers(kw)	2,50kW*1
Semi Rapid Gas Burners		1,70kW*2
Auxiliary Gas Burners		0,90kW*1
Triple Crown Burners		x
Down Cavity Oven Gas Burner		x
Down Cavity Grill Gas Burner		x
Hot Plate 145mm		X
Hot Plate 145mm		X
Hot Plate 180mm		X
Hi-Lite 140mm		X
Hi-Lite 180mm		X
Booster 160mm		X
Booster 180mm		X
Cavity Elc Top Heating Element		650W
Cavity Elc Bottom Heating Element		800W
Cavity Elc Grill Heating Element		X
Cavity Elc Spiral Heating Element	X	
Control Panel		
Oven Controller	Function Switch/Gas Valve	Function Switch
Knob Material	Plastic	Black
Knob Frame Material	Plastic	Black
Front Door		
Oven Door	Fixed Double Glass/Removable Double Glass	Fixed Double Glass
Handle	Color Painted /Brushed Al./ Rustic	Grey Painted
Oven		
Oven Interior (cavity)	Main material of cavity	Black Enamelled
Rack System (side panels of cavity)	Embossed /Chrome wire rack	Embossed
Self Clean	Catalytic	X
Cooling Fan		X
Temperature Range	Celsius Degree (°C) - THERMOSTAT	√
Convection	Static / Convectional (With Turbo Fan)	X
Flame Failure Device(FFSD)	Safety (Thermocouple)	X
Isolation Material		Special Knauf Isolation
Drawer And Bottom Part of Cooker		
Bottom Fascia	Flap Type / Sliding Drawer type / Fixed type	Fixed type
Oven Feet	Plastic / Metal Screw Feet	Plastic Screw Feet
Accessories		
Down Cavity Baking Tray	Enamelled (Shallow / Deep)	1 pc (Shallow)
Down Cavity Wire Inner Grid	Chrome Coated	1 pc
Tray Holder	Chrome Coated	X
Top Grid for Hob	Enamelled Grid/ Mat Enamelled Grid	Enamelled Grid
Power Cord		√
Plug	Type of plug: ie.EU,BS....	EU
Rotisserie		X
Timer	Mechanical/Digital	X
Wall Fixing Chain		√