

FCS-3306 HUBBLE Fixed Dome IP Camera, H.265, 3-MP

Product Images



Short Description

- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark

environments

- Built-in infrared LEDs for night viewing up to 30m
- 60 fps High Frame Rate (HFR) video in 1080p
- 3-Megapixel high-definition resolution
- Video compression: H.264, H.265
- Vandal-proof IK10-rated housing
- Weatherproof IP68-rated housing

Description

The LevelOne FCS-3306 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP68 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-3306 offers 3-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Additional Information

Fast Ethernet RJ45	10/100 Mbps,PoE 802.3af
Terminal block	DI/DO,
3.5mm audio in/out	Audio In/Audio Out
Harmonized System (HS) code	852589
Customs product code (TARIC)	8525890000
Features	Object Based Motion Detection, Tamper, Shock Detection, Line Crossing*, Enter Area*, Missing Object*, Unattended Object*, Smoke Detection*, Fire Detection* (Some of the algorithms may not be available in the first release, can be upgraded for free later)
PoE Supported	Yes
2-way audio	Yes
DI/DO	Yes
IR LED for night vision	Yes
Max. Resolution	3 Megapixels
Resistance	Weatherproof, Vandalproof
IP Camera series	HUBBLE
Camera Type	Dome
Zoom type	Fixed
Operating temperature	-40°C ~ 60°C
Supported browsers	IE 11or newer, Firefox with VLC, Chrome with VLC, Safari with QuickTime
Storage temperature	0°C ~ 80°C
Approval and Compliance	CF/FCC/UL,IK10,IP68
Package Contents	FCS-3306 Screw Kit Quick Installation Guide Resource CD (User Manual, Utility, QIG)
Product weight (kg)	0,835
Dimensions (W x D x H)	115 x 115 x 87 mm

Color	White
EAN	4015867202739
Model Number	FCS-3306
Power consumption	12.95 W (PoE)
Power supply	VDC12V/1A, PoE 802.3af
Power supply included	No
Resolution	30 fps at 2048 x 1536 60 fps at 1920 x 1080 30 fps at 1280 x 960 60 fps at 1280 x 720 30 fps at 800 x 600 30 fps at 640 x 480 30 fps at 320 x 240
Shutter time	1/5-1/64000
Standard	IPv4/v6, TCP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, NTP, RTP, RTSP, RTCP, SMTP, FTP, IGMP, ICMP, ARP, Bonjour, UPnP, QoS, SNMP, IEEE 802.1X
Storage capacity	MicroSDHC, MicroSDXC memory card slot (card not included)
Video format	H.265/H.264/MJPEG
Angle of view (°)	129
Digital zoom	4X
Image sensor	1/2.8 " Progressive Scan CMOS
Indicators	Power
IR cut filter	Yes
IR range	Up to 30 meter
Lens	Fixed focal, f2.1mm, F1.8
Minimum illumination (lux)	Color: 0.1 lux at F1.8 (30 IRE, Max. AGC); B/W: 0 (IR LED on)

