

Specs

Net Weight

23.6 lb (10.7 kg)

Dimensions

14.9 × 7.2 × 9.4 in (37.8 ×18.4 × 24 cm)

Charge Method

AC Wall Outlet, 12V Car Outlet, Solar Panel

Full Recharge Time

1.6 Hours (AC) 9½ Hours (12/24V Car Outlet) 3¾–7½ Hours (Using 2x 160W Solar Panels) 3–6 hours (Using 1x 400W Solar Panel)

Capacity

882Wh

Cell Chemistry

NCM Li-ion

Shelf Life

1 year (after fully charged)

Cycle Life

800 cycles to 80% capacity

Battery Management System

Over Voltage Protection, Overload Protection, Over Temperature Protection, Short Circuit Protection, Low Temperature Protection, Low Voltage Protection, Overcurrent Protection

Testing and certification

UL, CE, FCC, RoHS, TELEC

AC Charge Input Power

X-Stream Fast Charge 900W max

Solar Charge Input

300W 11–75V DC 10A max

Car Charger

12V/24V DC 8A default

AC Output (×5)

Pure Sine Wave, 1400W total (surge 2100W), 120V~ (50Hz/60Hz)

USB-A Output (×2)

5V DC, 2.4A, 12W Max, per port

USB-A Fast Charge (×1)

5V, 2.4A / 9V, 2A / 12V, 1.5A, 18W Max

USB-C Output

5/9/12/15/20V, 5A, 100W Max

Car Power Output

12.6V, 10A, 126W Max