

FCS-3461, GEMINI Zoom IP Camera, 2-MP, 4x Zoom, H.265, INDOOR/OUTDOOR

Product Images



Short Description

- 2-Megapixel high-definition resolution
- Built-in Micro SD/SDHC/SDXC card slot for local storage
- Built-in infrared LEDs for night viewing up to 30m
- Video compression: H.264, H.265, MJPEG
- Weatherproof IP67-rated housing
- Features WDR (Wide Dynamic Range) 120 dB to enhance visibility under extremely bright or dark environments

Description

The LevelOne FCS-3461 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-3461 Should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Additional Information

Harmonized System (HS) code	852589
Customs product code (TARIC)	8525890000
Features	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark Region of Interest:1 fixed region for main stream and sub-stream Saturation, brightness, contrast, sharpness, AGC, White balance adjustable by client software or web browser BLC, 3D DNR Basic Event : Motion detection, video tampering alarm, exception Smart Event : Line crossing detection, intrusion detection
PoE Supported	Yes
2-way audio	No
DI/DO	No
IR LED for night vision	Yes
Max. Resolution	2 Megapixels
Resistance	Weatherproof, Vandalproof
IP Camera series	GEMINI
Camera Type	Dome
Zoom type	Motorization
Operating humidity	5% RH ~ 95% RH
Operating temperature	-30°C ~ 60°C
Package Content	Screw kits
Supported browsers	Plug-in required live view: IE 10+ Plug-in free live view: Chrome 57.0+, Firefox 52.0+ Local service: Chrome 57.0+, Firefox 52.0+
Approval and Compliance	CE/FCC/IP67
Package Contents	Screw Kit Declaration of Conformity
Product weight (kg)	1.3
Dimensions (W x D x H)	Ø153 .3 mm × 111.6 mm (6" × 4.4 ")
Color	White

EAN	4015867238493
Model Number	FCS-3461
Optical zoom	4X
Port Configuration	RJ-45(PoE) / Power
Power consumption	12 VDC $\pm$ 25%, 0.8 A, max. 10 W, Ø5.5 mm coaxial power plug PoE: (802.3af, Class 3, 36 V to 57 V), 0.21 A to 0.33 A, max. 12 W
Power supply included	No
Resolution	Main Stream 50 Hz: 25 fps (1920 $\times$ 1080, 1280 $\times$ 720) 60 Hz: 30 fps (1920 $\times$ 1080, 1280 $\times$ 720) Sub-Stream 50 Hz: 25 fps (640 $\times$ 480, 640 $\times$ 360) 60 Hz: 30 fps (640 $\times$ 480, 640 $\times$ 360)
Shutter time	1/3 s to 1/100,000 s
Standard	IEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3af Power over Ethernet (PoE) IEEE 802.1X Network Access Control TCP(IPv6/v4), UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP,FTP,SAMBA UPnP, SNMP, Bonjour
Storage capacity	Built-in memory card slot, support microSD card, up to 256 GB
Video format	H.265/H.264/MJPEG
Weatherproof rating	IP67
Angle of view (°)	Horizontal FOV 98° to 38°, Vertical FOV 52° to 21°, Diagonal FOV 115° to 43°
Digital zoom	16x
Image sensor	1/2.7" Progressive Scan CMOS
Indicators	Power/Act
IR cut filter	Yes
IR range	30 Meter
Lens	Motorized lens, 2.8 to 12 mm ,F1.6
Minimum illumination (lux)	Color: 0.005 Lux @(F1.6, AGC ON), B/W: 0 Lux with IR
Mount	Ceiling mount

