


FCS-3402 GEMINI Fixed Dome IP Network Camera, 2- Megapixel, H.265, Vandalproof, 802.3af PoE, Indoor/Outdoor

Product Images



Short Description

- Video compression: H.264, H.265, MJPEG
- Weatherproof IP67-rated housing
- Built-in Micro SDHC/SDXC card slot for local storage
- Supports iPhone/Android phone remote viewing over the Internet

Description

The LevelOne FCS-3402 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-3402 Should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Additional Information

Code des Harmonisierten Systems (HS)	852589
Zolltariflicher Warencode (TARIC)	8525890000
Features	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark Region of Interest:1 fixed region for main stream and sub-stream Saturation, brightness, contrast, sharpness, AGC, White balance adjustable by client software or web browser BLC, 3D DNR Motion detection, video tampering alarm, illegal login
PoE Supported	Ja
2-way audio	Ja
DI/DO	Ja
IR LED for night vision	Ja
Max. Resolution	2 Megapixels
Resistance	Weatherproof
IP Camera series	GEMINI
Camera Type	Dome
Zoom type	Fixed
Operating humidity	0% RH ~ 95% RH
Operating temperature	-30°C ~ 60°C
Inhalt des Pakets	Quick installation guide
Unterstützte Browser	Plug-in required live view: IE 10+ Plug-in free live view: Chrome 57.0+, Firefox 52.0+ Local service: Chrome 57.0+, Firefox 52.0+
Storage humidity	0% RH ~ 95% RH
Storage temperature	-30°C ~ 70°C
Zulassungen und Konformität	CE/FCC,IP67, IK10
Kompatibilität	CE/FCC
Lieferumfang	FCS-3402 Screw Kit Quick Installation Guide
Produktgewicht (kg)	0.5

Dimensions (W x D x H)	135 mm × 135 mm × 110 mm (5.3" × 5.3" × 4.3")
Farbe	Weiß
EAN	4015867231289
Modellnummer	FCS-3402
Port Configuration	RJ-45(PoE) ,DI/DO, Power
Energieverbrauch	12 VDC, 0.4 A, Max: 5 W PoE: (802.3af, 37 V to 57 V), 0.2 A to 0.13 A, Max: 7 W
Stromversorgung	PoE/VDC 12V
Power supply included	Nein
Auflösung	Main Stream: 50Hz: 25fps (1920 * 1080, 1280 * 960, 1280 * 720) 60Hz: 30fps (1920 * 1080, 1280 * 960, 1280 * 720) Sub-Stream: 50Hz: 25fps (640 * 480, 640 * 360, 320 * 240) 60Hz: 30fps (640 * 480, 640 * 360, 320 * 240)
Verschlusszeit	1/3 s to 1/100,000 s
Standards	IEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3af Power over Ethernet (PoE) IEEE 802.1X Network Access Control TCP(IPv6/v4), UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP,FTP,SAMBA UPnP, SNMP, Bonjour
Speicherkapazität	MicroSDHC /MicroSDXC card slot for local storage (256Gb)
Videoformat	H.265/H.264/MJPEG
Wetterfestigkeit	IP67
Betrachtungswinkel	FOV 91.5°, vertical FOV 46.1°, diagonal FOV 109.8°
Digital-Zoom	8x
Bildsensor	1/2.8" Progressive Scan CMOS
Indikator	Power
IR Sperrfilter	Ja
Infrarotdistanz in m	Up to 30 meter
Linse	Board LENS 4mm @F1.6
Minimale Beleuchtung (Lux)	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR

