PEG 18

COMFORT INSTANTANEOUS WATER HEATERS

PRODUCT-NO.: 233995



Rely on a constant output
This instantaneous water heater makes things particularly easy for you. The two-stage selection determines the temperature at which the water comes out of the tap. You can specify one of two temperatures using a rotary selector. Once set, you can rely on it completely.

Carefree warm water Our appliance reliably maintains the selected temperature thanks to its electronic control system. In addition, it indicates when you are at risk of scalding. So there is nothing to stop you enjoying soothing warm water every single day.



PEG 13
Product-No.: 233994



PEG 21
Product-No.: 233996

The main features

- Highly convenient thanks to electronic control
- Consistent temperature delivery up to the maximum output
- Two-stage temperature setting with application symbols
- Scale-resistant bare wire heating system





Type	PEG 13	PEG 18	PEG 21
Part no.	233994	233995	233996

Technical data

Rated voltage	400 V	400 V	400 V
Rated voltage 1	380 V	380 V	380 V
Rated voltage 2	400 V	400 V	400 V
Rated output	13,5 kW	18 kW	21 kW
Rated output 1	12,2 kW	16,2 kW	19 kW
Rated output 2	13,5 kW	18 kW	21 kW
Rated current	19,5 A	26 A	31 A
Rated current 1	18,5 A	24,7 A	29,5 A
Rated current 2	19,5 A	26 A	31 A
Fuse protection	20 A	25 A	32 A
Fuse protection 1	20 A	25 A	32 A
Fuse protection 2	20 A	25 A	32 A
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 1	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Phases	3/PE	3/PE	3/PE
Conductivity σ15 ≤	909 µS/cm	909 µS/cm	909 µS/cm
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 380 V)	900 µS/cm	900 µS/cm	900 µS/cm
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C and 400 V)	900 µS/cm	900 µS/cm	900 µS/cm
Resistivity ρ15 ≥	1100 Ω cm	1100 Ω cm	1100 Ω cm
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 380 V)	1100 Ω cm	1100 Ω cm	1100 Ω cm

Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C and 400 V)	1100 Ω cm	1100 Ω cm	1100 Ω cm
Switch-on water flow rate	>3,0 l/min	>3,0 l/min	>3,0 l/min
Temperature setting	42-55 °C	42-55 °C	42-55 °C
Colour	white	white	white
Height	485 mm	485 mm	485 mm
Width	226 mm	226 mm	226 mm
Depth	93 mm	93 mm	93 mm
Weight	3.60 kg	3.60 kg	3.60 kg
Energy efficiency class (A+ → F)	A	A	A

Contact information

You have questions? We appreciate to help you:
Call **+49 5531 - 7020**
Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.