

FCS-5095, GEMINI ZOOM IP CAMERA, 8-MP, H.265, 802.3AT, POE, IR LEDS, INDOOR/OUTDOOR, TWO-WAY AUDIO

Product Images



Other models: FCS-5092 FCS-5095 FCS-5093 FCS-5096 FCS-5095v2 FCS-5098 FCS-5212v2 FCS-5201 FCS-5202			
			
Model	FCS-5092	FCS-5095	FCS-5098
Type	IP67-rated	IP67-rated	IP67-rated
Description	8MP, 802.3AT, PoE, IR LEDS, TWO-WAY AUDIO	8MP, 802.3AT, PoE, IR LEDS, TWO-WAY AUDIO	8MP, 802.3AT, PoE, IR LEDS, TWO-WAY AUDIO
			
Model	FCS-5201		
Type	IP67-rated		
Description	8MP, 802.3AT, PoE, IR LEDS, TWO-WAY AUDIO		

Short Description

- 8-Megapixel high-definition resolution
- Built-in infrared LEDs for night viewing up to 60m
- Dual power support: 12V DC/PoE (IEEE 802.3at)
- Video compression: H.264, H.265, MJPEG
- Weatherproof IP67-rated housing
- Vandal-proof IK10-rated housing

- Supports 4.3X optical zoom

Description

The LevelOne FCS-5095 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 8-Megapixel resolution and the versatility of 802.3at standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5095 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Additional Information

Harmonized System (HS) code	852589
Customs product code (TARIC)	8525890000
Features	Basic Event: Motion detection (support alarm triggering by specified target types (human and vehicle)),video tampering alarm,exception Smart Event: Face detection,Line crossing detection, intrusion detection (support alarm triggered by specified target types (human and vehicle)) Linkage: Upload to FTP/NAS/memory card,notify surveillance center,send email,trigger recording,trigger capture
PoE Supported	Yes
2-way audio	Yes
DI/DO	Yes
IR LED for night vision	Yes
Max. Resolution	8 Megapixels
Resistance	Weatherproof
IP Camera series	GEMINI
Camera Type	Bullet
Zoom type	Motorization
Operating humidity	5% RH ~ 95% RH
Operating temperature	-30°C ~ 60°C
Supported browsers	Plug-in required live view: IE 10, IE 11,Edge Plug-in free live view: Chrome 57.0+, Firefox 52.0+, Edge 89+, Local service: Chrome 57.0+, Firefox 52.0+, Edge 89+
Compatible operating systems	Option accessory Mounting Kit : CAS-7303 Pole Mount CAS-7307 Corner mount CAS-7311 Junction Box CAS-7312 Power intake box
Storage humidity	5% RH ~ 95% RH
Storage temperature	-30°C ~ 70°C
Approval and Compliance	CE/FCC/UL
Compatibility	Onvif

Package Contents	Screw Kit QIG
Product weight (kg)	1.385
Dimensions (W x D x H)	385x190x180
Color	White
EAN	4015867228654
Model Number	FCS-5095
Optical zoom	4.3X Zoom, 2.8-12mm LENS
Port Configuration	RJ-45, DI/DO (terminal block), Audio In/Out (terminal block)
Power consumption	12 VDC $\pm$ 25%, 1.08 A, max. 13 W, Ø5.5 mm coaxial power plug, reverse polarity protection, PoE: 802.3at, Class 4, 42.5 V to 57 V, 0.36 A to 0.27 A, max. 15 W
Power supply included	No
Resolution	Main Stream 50 Hz: 20 fps (3840 × 2160) 25 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 20 fps (3840 × 2160) 30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
Shutter time	1/3 s to 1/100,000 s
Standard	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, ARP, WebSocket, WebSockets
Storage capacity	Build-in Micro SD Card slot support up to 256 GB
Video format	H.265/H.264/MJPEG
Weatherproof rating	IP67
Angle of view (°)	FOV 108° to 30°, vertical FOV 56° to 17°, diagonal FOV 131° to 35°
Audio format	G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC
Digital zoom	8
Image sensor	1/2.8" Progressive Scan CMOS
Indicators	Power /Link Act
IR cut filter	Yes

IR range	Up to 60 Meter
Lens	Motorized lens, 2.8 to 12 mm
Minimum illumination (lux)	Color: 0.005 Lux @ (F1.6, AGC ON),B/W: 0 Lux with IR
Mount	Wall mount

