This site uses cookies. By continuing to browse the site you are agreeing to our use of cookies.
FIND OUT MORE HERE >

PM1733

MZWLJ1T9HBJR-00007



Best-in-class for enterprise

Samsung's all-flash solutions for heavy workloads deliver unrivaled performance, reliability and capacity without bottlenecks.

Specifications

Model	PM1733	Interface	PCIe Gen4 x4/dual port x2
F/F	2.5 inch	Capacity	1.92 TB
Seq. Read	7000 MB/s	Seq. Write	2400 MB/s
Ran. Read	800K IOPS	Ran. Write	100K IOPS
DWPD	1(5yrs)	Product Status	Mass Production

SEE ALL

Related insights

Downloaded from Arrow.com.



The Stay-at-Home Trend and Its Implications for Data Centers

Find out how the stay-at-home trend has highlighted a need for faster and more efficient data center solutions.

LEARN MORE >



All-Flash NVMe Reference Architecture with Red Hat Ceph

Samsung designed Ceph clusters based on all-flash NVMe SSDs and conducted various tests to provide Ceph users with optimized Ceph configurations.

LEARN MORE >

All product specifications reflect internal test results and are subject to variations by user's system configuration. All product images shown are for illustration purposes only and may not be an exact representation of the product. Samsung reserves the right to change product images and specifications at any time without notice.

Copyright © 1995-2020 SAMSUNG All Rights Reserved.

This website is best viewed using Microsoft Internet Explorer 9 or higher, and/or latest version of Google Chrome and Mozila Firefox browsers.

Downloaded from Arrow.com.